



PACKAGE DIMENSIONS




NOTES:

1. Dimensions for all drawings are in inches (mm).
2. Tolerance of $\pm .010$ (.25) on all non-nominal dimensions unless otherwise specified.



SCHEMATIC



DESCRIPTION

The H24A series consists of a gallium arsenide infrared emitting diode coupled with a silicon phototransistor. The devices are housed in a low cost plastic package with lead spacing compatible with a dual in line package.

FEATURES

- 4-pin configuration
- Small package size and low cost
- UL recognized - file E50151

H24A1

H24A2

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Operating Temperature	T_{OPR}	-55 to +85	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 to +85	$^\circ\text{C}$
Soldering Temperature (Flow)	T_{SOL-F}	260 for 5 sec	$^\circ\text{C}$
EMITTER			
Power Dissipation at 25°C Ambient ⁽¹⁾	P_D	100	mW
Continuous Forward Current	I_F	60	mA
Reverse Voltage	V_R	4	V
DETECTOR			
Power Dissipation 25°C Ambient ⁽²⁾	P_D	150	mW
Collector to Emitter Voltage	V_{CEO}	30	V
Emitter to Collector Voltage	V_{ECO}	6	V
Continuous Forward Current	I_C	100	mA

ELECTRICAL / OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

INDIVIDUAL COMPONENT CHARACTERISTICS

Parameters	Test Conditions	Symbol	Min	Typ	Max	Units
EMITTER						
Forward Voltage	$I_F = 60 \text{ mA}$	V_F		–	1.7	V
Reverse Current	$V_R = 3.0 \text{ V}$	I_R		–	1	μA
Reverse Breakdown Voltage	$I_R = 10 \mu\text{A}$	$V_{(BR)R}$	4			V
Capacitance	$V = 0 \text{ V}, f = 1 \text{ MHz}$	C		30		pF
DETECTOR						
Breakdown Voltage Collector to Emitter	$I_C = 1.0 \text{ mA}, I_F = 0$	BV_{CEO}	30			V
Emitter to Collector	$I_E = 100 \mu\text{A}, I_F = 0$	BV_{ECO}	7			V
Leakage Current Collector to Emitter	$V_{CE} = 10 \text{ V}, I_F = 0$	I_{CEO}		5	100	nA
Capacitance Collector to Emitter	$V_{CE} = 5 \text{ V}, f = 1 \text{ MHz}$	C_{CE}		3.3		pF

NOTE:

1. Derate power linearly 1.67 mW/ $^\circ\text{C}$ above 25°C
2. Derate power linearly 2.5 mW/ $^\circ\text{C}$ above 25°C

H24A1

H24A2

TRANSFER CHARACTERISTICS (T_A = 25°C Unless otherwise specified.)

DC Characteristics	Test Conditions	Symbol	Min	Typ	Max	Units
COUPLED DC current Transfer Ratio (note 1)	V _{CE} = 10 V, I _F = 10 mA	H24A1	CTR	100		%
		H24A2		20		
Saturation Voltage	I _C = 500 µA, I _F = 10 mA	V _{CE(SAT)}		0.1	0.4	V
AC Characteristics	Test Conditions	Symbol	Min	Typ	Max	Units
Turn-on Time	I _C = 2mA, V _{CE} = 10V R _L = 100Ω	ton		9		µs
Turn-off Time		toff		4		µs
Turn-on Time	I _F = 10mA, V _{CC} = 5V R _L = 10kΩ	ton		6.5		µs
Turn-off Time		toff		165		µs

ISOLATION CHARACTERISTICS

Characteristic	Test Conditions	Symbol	Min	Typ	Max	Units
Surge Isolation Voltage	1 Minute	V _{ISO}	6000			V _{peak}
Steady-State Isolation Voltage	1 Minute	V _{ISO}	5300			V _{RMS}
Isolation Resistance	V _{I-0} = 500VDC	R _{ISO}	10 ¹¹			Ohm
Isolation Capacitance	V _{I-0} = 0, f = 1 MHz	C _{ISO}		0.5		pF

NOTE:

1. The current transfer ratio (I_C/I_F) is the ratio of the detector collector current to the LED input current with V_{CE} at 10 volts.

H24A1

H24A2




Fig. 1. Output Current vs. Input Current




Fig. 2. Output Current vs. Temperature




Fig. 3. Input Characteristics




Fig. 4. Output Characteristics




Fig. 5. Switching Speed vs. R_L




Fig. 6. Leakage Current vs. Temperature

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.