



**38A, 200V, 0.071 Ohm, N-Channel,  
UltraFET® Power MOSFETs**

**Packaging**



**Symbol**



**Features**

- Ultra Low On-Resistance
  - $r_{DS(ON)} = 0.071\Omega$ ,  $V_{GS} = 10V$
- Simulation Models
  - Temperature Compensated PSPICE® and SABER™ Electrical Models
  - Spice and SABER Thermal Impedance Models
  - [www.fairchildsemi.com](http://www.fairchildsemi.com)
- Peak Current vs Pulse Width Curve
- UIS Rating Curve

**Ordering Information**

| PART NUMBER  | PACKAGE  | BRAND  |
|--------------|----------|--------|
| HUF75945G3   | TO-247   | 75945G |
| HUF75945P3   | TO-220AB | 75945P |
| HUF75945S3ST | TO-263AB | 75945S |

NOTE: When ordering, use the entire part number.

**Absolute Maximum Ratings**  $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

|                                                                                |                |
|--------------------------------------------------------------------------------|----------------|
| Drain to Source Voltage (Note 1) . . . . .                                     | $V_{DSS}$      |
| Drain to Gate Voltage ( $R_{GS} = 20k\Omega$ ) (Note 1) . . . . .              | $V_{DGR}$      |
| Gate to Source Voltage . . . . .                                               | $V_{GS}$       |
| Drain Current                                                                  |                |
| Continuous ( $T_C = 25^\circ\text{C}$ , $V_{GS} = 10V$ ) (Figure 2) . . . . .  | $I_D$          |
| Continuous ( $T_C = 100^\circ\text{C}$ , $V_{GS} = 10V$ ) (Figure 2) . . . . . | $I_D$          |
| Pulsed Drain Current . . . . .                                                 | $I_{DM}$       |
| Pulsed Avalanche Rating . . . . .                                              | UIS            |
| Power Dissipation . . . . .                                                    | $P_D$          |
| Derate Above $25^\circ\text{C}$ . . . . .                                      |                |
| Operating and Storage Temperature . . . . .                                    | $T_J, T_{STG}$ |
| Maximum Temperature for Soldering                                              |                |
| Leads at 0.063in (1.6mm) from Case for 10s. . . . .                            | $T_L$          |
| Package Body for 10s, See Techbrief TB334. . . . .                             | $T_{pkg}$      |

NOTES:

1.  $T_J = 25^\circ\text{C}$  to  $150^\circ\text{C}$ .

**CAUTION:** Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

| HUF75945G3, HUF75945P3,<br>HUF75945S3ST | UNITS              |
|-----------------------------------------|--------------------|
| 200                                     | V                  |
| 200                                     | V                  |
| $\pm 20$                                | V                  |
| 38                                      | A                  |
| 27                                      | A                  |
| Figure 4                                |                    |
| Figures 6, 14, 15                       |                    |
| 310                                     | W                  |
| 2.07                                    | $W/^\circ\text{C}$ |
| -55 to 175                              | $^\circ\text{C}$   |
| 300                                     | $^\circ\text{C}$   |
| 260                                     | $^\circ\text{C}$   |

# HUF75945G3, HUF75945P3, HUF75945S3ST

## Electrical Specifications $T_C = 25^{\circ}\text{C}$ , Unless Otherwise Specified

| PARAMETER                                        | SYMBOL              | TEST CONDITIONS                                                                                                      | MIN                                                                                                     | TYP   | MAX   | UNITS |    |
|--------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|-------|-------|-------|----|
| OFF STATE SPECIFICATIONS                         |                     |                                                                                                                      |                                                                                                         |       |       |       |    |
| Drain to Source Breakdown Voltage                | BV <sub>DSS</sub>   | I <sub>D</sub> = 250μA, V <sub>GS</sub> = 0V (Figure 11)                                                             | 200                                                                                                     | -     | -     | V     |    |
| Zero Gate Voltage Drain Current                  | I <sub>DSS</sub>    | V <sub>DS</sub> = 190V, V <sub>GS</sub> = 0V                                                                         | -                                                                                                       | -     | 1     | μA    |    |
|                                                  |                     | V <sub>DS</sub> = 180V, V <sub>GS</sub> = 0V, T <sub>C</sub> = 150°C                                                 | -                                                                                                       | -     | 250   | μA    |    |
| Gate to Source Leakage Current                   | I <sub>GSS</sub>    | V <sub>GS</sub> = ±20V                                                                                               | -                                                                                                       | -     | ±100  | nA    |    |
| ON STATE SPECIFICATIONS                          |                     |                                                                                                                      |                                                                                                         |       |       |       |    |
| Gate to Source Threshold Voltage                 | V <sub>GS(TH)</sub> | V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 250μA (Figure 10)                                               | 2                                                                                                       | -     | 4     | V     |    |
| Drain to Source On Resistance                    | r <sub>DS(ON)</sub> | I <sub>D</sub> = 38A, V <sub>GS</sub> = 10V (Figure 9)                                                               | -                                                                                                       | 0.056 | 0.071 | ¾     |    |
| THERMAL SPECIFICATIONS                           |                     |                                                                                                                      |                                                                                                         |       |       |       |    |
| Thermal Resistance Junction to Case              | R <sub>θJC</sub>    | TO-247, TO-220, TO-263                                                                                               | -                                                                                                       | -     | 0.48  | °C/W  |    |
| Thermal Resistance Junction to Ambient           | R <sub>θJA</sub>    | TO-247                                                                                                               | -                                                                                                       | -     | 30    | °C/W  |    |
|                                                  |                     | TO-220, TO-263                                                                                                       | -                                                                                                       | -     | 62    | °C/W  |    |
| SWITCHING SPECIFICATIONS (V <sub>GS</sub> = 10V) |                     |                                                                                                                      |                                                                                                         |       |       |       |    |
| Turn-On Time                                     | t <sub>ON</sub>     | V <sub>DD</sub> = 100V, I <sub>D</sub> = 38A<br>V <sub>GS</sub> = 10V,<br>R <sub>GS</sub> = 3.0Ω<br>(Figures 18, 19) | -                                                                                                       | -     | 33    | ns    |    |
| Turn-On Delay Time                               | t <sub>d(ON)</sub>  |                                                                                                                      | -                                                                                                       | 15    | -     | ns    |    |
| Rise Time                                        | t <sub>r</sub>      |                                                                                                                      | -                                                                                                       | 64    | -     | ns    |    |
| Turn-Off Delay Time                              | t <sub>d(OFF)</sub> |                                                                                                                      | -                                                                                                       | 65    | -     | ns    |    |
| Fall Time                                        | t <sub>f</sub>      |                                                                                                                      | -                                                                                                       | 80    | -     | ns    |    |
| Turn-Off Time                                    | t <sub>OFF</sub>    |                                                                                                                      | -                                                                                                       | -     | 217   | ns    |    |
| GATE CHARGE SPECIFICATIONS                       |                     |                                                                                                                      |                                                                                                         |       |       |       |    |
| Total Gate Charge                                | Q <sub>g(TOT)</sub> | V <sub>GS</sub> = 0V to 20V                                                                                          | V <sub>DD</sub> = 100V,<br>I <sub>D</sub> = 38A,<br>I <sub>g(REF)</sub> = 1.0mA<br>(Figures 13, 16, 17) | -     | 215   | 280   | nC |
| Gate Charge at 10V                               | Q <sub>g(10)</sub>  | V <sub>GS</sub> = 0V to 10V                                                                                          |                                                                                                         | -     | 118   | 153   | nC |
| Threshold Gate Charge                            | Q <sub>g(TH)</sub>  | V <sub>GS</sub> = 0V to 2V                                                                                           |                                                                                                         | -     | 8     | 10    | nC |
| Gate to Source Gate Charge                       | Q <sub>gs</sub>     |                                                                                                                      |                                                                                                         | -     | 15    | -     | nC |
| Gate to Drain “Miller” Charge                    | Q <sub>gd</sub>     |                                                                                                                      |                                                                                                         | -     | 42    | -     | nC |
| CAPACITANCE SPECIFICATIONS                       |                     |                                                                                                                      |                                                                                                         |       |       |       |    |
| Input Capacitance                                | C <sub>ISS</sub>    | V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V,<br>f = 1MHz (Figure 12)                                                 | -                                                                                                       | 4023  | -     | pF    |    |
| Output Capacitance                               | C <sub>OSS</sub>    |                                                                                                                      | -                                                                                                       | 880   | -     | pF    |    |
| Reverse Transfer Capacitance                     | C <sub>RSS</sub>    |                                                                                                                      | -                                                                                                       | 240   | -     | pF    |    |

## Source to Drain Diode Specifications

| PARAMETER                     | SYMBOL   | TEST CONDITIONS                                                | MIN | TYP | MAX  | UNITS |
|-------------------------------|----------|----------------------------------------------------------------|-----|-----|------|-------|
| Source to Drain Diode Voltage | $V_{SD}$ | $I_{SD} = 38\text{A}$                                          | -   | -   | 1.25 | V     |
|                               |          | $I_{SD} = 19\text{A}$                                          | -   | -   | 1.00 | V     |
| Reverse Recovery Time         | $t_{rr}$ | $I_{SD} = 38\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 281  | ns    |
| Reverse Recovered Charge      | $Q_{RR}$ | $I_{SD} = 38\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 2700 | nC    |

## Typical Performance Curves




FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE




FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 3. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE




FIGURE 4. PEAK CURRENT CAPABILITY

Typical Performance Curves (Continued)





FIGURE 5. FORWARD BIAS SAFE OPERATING AREA



NOTE: Refer to Fairchild Application Notes AN9321 and AN9322.

FIGURE 6. UNCLAMPED INDUCTIVE SWITCHING CAPABILITY




FIGURE 7. TRANSFER CHARACTERISTICS




FIGURE 8. SATURATION CHARACTERISTICS




FIGURE 9. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE




FIGURE 10. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE

## Typical Performance Curves (Continued)




FIGURE 11. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE





FIGURE 12. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



NOTE: Refer to Fairchild Application Notes AN7254 and AN7260.

FIGURE 13. GATE CHARGE WAVEFORMS FOR CONSTANT GATE CURRENT

## Test Circuits and Waveforms




FIGURE 14. UNCLAMPED ENERGY TEST CIRCUIT




FIGURE 15. UNCLAMPED ENERGY WAVEFORMS

Test Circuits and Waveforms (Continued)




FIGURE 16. GATE CHARGE TEST CIRCUIT




FIGURE 17. GATE CHARGE WAVEFORMS




FIGURE 18. SWITCHING TIME TEST CIRCUIT




FIGURE 19. SWITCHING TIME WAVEFORM





## SPICE Thermal Model

REV 13 October 2000

HUF75945T

CTHERM1 th 6 6.45e-3  
 CHERM2 6 5 3.00e-2  
 CHERM3 5 4 1.40e-2  
 CHERM4 4 3 1.65e-2  
 CHERM5 3 2 4.85e-2  
 CHERM6 2 tl 1.00e-1


RHERM1 th 6 3.24e-3  
 RHERM2 6 5 8.08e-3  
 RHERM3 5 4 2.28e-2  
 RHERM4 4 3 1.00e-1  
 RHERM5 3 2 1.10e-1  
 RHERM6 2 tl 1.40e-1

## SABER Thermal Model

SABER thermal model HUF75945T

```
template thermal_model th tl
thermal_c th, tl
{
    ctherm.ctherm1 th 6 = 6.45e-3
    ctherm.ctherm2 6 5 = 3.00e-2
    ctherm.ctherm3 5 4 = 1.40e-2
    ctherm.ctherm4 4 3 = 1.65e-2
    ctherm.ctherm5 3 2 = 4.85e-2
    ctherm.ctherm6 2 tl = 1.00e-1

    rtherm.rtherm1 th 6 = 3.24e-3
    rtherm.rtherm2 6 5 = 8.08e-3
    rtherm.rtherm3 5 4 = 2.28e-2
    rtherm.rtherm4 4 3 = 1.00e-1
    rtherm.rtherm5 3 2 = 1.10e-1
    rtherm.rtherm6 2 tl = 1.40e-1
}
```



## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                      |                     |                              |                       |      |
|----------------------|---------------------|------------------------------|-----------------------|------|
| ACE <sup>Ex</sup> ™  | FAST <sup>®</sup>   | OPTOLOGIC™                   | SMART START™          | VCX™ |
| Bottomless™          | FAST <sup>r</sup> ™ | OPTOPLANAR™                  | STAR*POWER™           |      |
| CoolFET™             | FRFET™              | PACMAN™                      | Stealth™              |      |
| CROSSVOLT™           | GlobalOptoisolator™ | POP™                         | SuperSOT™-3           |      |
| DenseTrench™         | GTO™                | Power247™                    | SuperSOT™-6           |      |
| DOME™                | HiSeC™              | PowerTrench <sup>®</sup>     | SuperSOT™-8           |      |
| EcoSPARK™            | ISOPLANAR™          | QFET™                        | SyncFET™              |      |
| E <sup>2</sup> CMOS™ | LittleFET™          | QS™                          | TinyLogic™            |      |
| EnSigna™             | MicroFET™           | QT Optoelectronics™          | TruTranslation™       |      |
| FACT™                | MicroPak™           | Quiet Series™                | UHC™                  |      |
| FACT Quiet Series™   | MICROWIRE™          | SILENT SWITCHER <sup>®</sup> | UltraFET <sup>®</sup> |      |

STAR\*POWER is used under license

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |