



UGF10A THRU UGF10K



SURFACE MOUNT GLASS PASSIVATED JUNCTION ULTRAFAST EFFICIENT RECTIFIER

Reverse Voltage - 50 to 800 Volts

Forward Current - 1.0 Ampere

PATENTED

DO-214AC



*Dimensions in inches and (millimeters)

SUPEREX IITM



FEATURES

- * GPRC (Glass Passivated Rectifier Chip) inside
- * Glass passivated cavity-free junction
- * Ideal for surface mount automotive applications
- * Ultrafast recovery time for high efficiency
- * Built-in strain relief
- * Easy pick and place
- * High temperature soldering guaranteed: 260°C/10 seconds, at terminals
- * Plastic package has Underwriters Laboratory Flammability Classification 94V-0

MECHANICAL DATA

Case : JEDEC DO-214AC molded plastic over passivated chip

Terminals : Solder plated , solderable per MIL-STD-750, Method 2026

Polarity : Color band denotes cathode end

Mounting Position : Any

Weight : 0.002 ounces , 0.064 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.	SYMBOLS	UGF10							UNITS
		A	B	D	F	G	J	K	
Maximum repetitive peak reverse voltage	VRRM	50	100	200	300	400	600	800	Volts
Maximum RMS voltage	VRMS	35	70	140	210	280	420	560	Volts
Maximum DC blocking voltage	VDC	50	100	200	300	400	600	800	Volts
Maximum average forward rectified current TA=55°C	I (AV)	1.0							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	IFSM	30					25		Amps
Maximum instantaneous forward voltage at 1.0 A	VF	0.95			1.25		1.7	2.2	Volts
Maximum DC reverse current TA=25°C at rated DC blocking voltage TA=125°C	IR	5 50							uA
Maximum reverse recovery time (NOTE 1)	trr	35							nS
Typical junction capacitance (NOTE 2)	CJ	10							pF
Typical thermal resistance (NOTE 3)	R θJA	34							°C / W
Operating junction and storage temperature range	TJ,TSTG	-55 to +150							°C

NOTES : (1) Reverse recovery test condition : IF 0.5A, IR=1.0A, Irr=0.25A

(2) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts

(3) Thermal resistance from junction to ambient and from junction to lead P.C.B. mounted on 0.2 x 0.2" (5.0 x 5.0mm) copper pad areas.

RATINGS AND CHARACTERISTIC CURVES UGF10A THRU UGF10K

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

