



Micro Commercial Components  
21201 Itasca Street Chatsworth  
CA 91311

Phone: (818) 701-4933

Fax: (818) 701-4939

## RB421D

### Features

- Low VF ( VF=0.45V Typ at 100mA )
- High reliability
- Small surface mounting type ( SMD3 )

### Mechanical Data

- Case :SOT-346,Molded Plastic
- Low power rectification
- Silicon epitaxial planar


### Maximum Ratings

- Operating Junction Temperature: 125°C
- Storage Temperature: -40°C to +125°C

| MCC Catalog Number | Device Marking | Maximum Recurrent Peak Reverse Voltage | Maximum RMS Voltage | Maximum DC Blocking Voltage |
|--------------------|----------------|----------------------------------------|---------------------|-----------------------------|
| RB421D             | D3C            | 40V                                    | 28V                 | 40V                         |

## 0.1 Amp Surface Mount Schottky Barrier Diode 40 Volts

### SOT-346




| DIM | INCHES |      | MM   |      | NOTE |
|-----|--------|------|------|------|------|
|     | MIN    | MAX  | MIN  | MAX  |      |
| A   | .106   | .122 | 2.70 | 3.10 |      |
| B   | .051   | .067 | 1.30 | 1.70 |      |
| C   | .039   | .051 | 1.00 | 1.30 |      |
| D   | .014   | .020 | 0.35 | 0.50 |      |
| G   | .067   | .091 | 1.70 | 2.30 |      |
| H   | .000   | .004 | 0.00 | 0.10 |      |
| J   | .004   | .010 | 0.10 | 0.26 |      |
| K   | .008   | .024 | 0.20 | 0.60 |      |
| L   | .049   | .065 | 1.25 | 1.65 |      |
| S   | .089   | .118 | 2.25 | 3.00 |      |

### Electrical Characteristics @ 25°C Unless Otherwise Specified

|                                                         |             |                |                                                                               |
|---------------------------------------------------------|-------------|----------------|-------------------------------------------------------------------------------|
| Average Forward Current                                 | $I_{F(AV)}$ | 0.1A           | $T_A = 25^\circ\text{C}$                                                      |
| Peak Forward Surge Current                              | $I_{FSM}$   | 1.0A           | 8.3ms, half sine                                                              |
| Maximum Forward Voltage                                 | $V_F$       | 0.55V<br>0.34V | $I_{FM} = 100\text{mA}$<br>$I_{FM} = 10\text{mA}$<br>$T_A = 25^\circ\text{C}$ |
| Maximum DC Reverse Current At Rated DC Blocking Voltage | $I_R$       | 30mA           | $T_A = 25^\circ\text{C}$<br>$V_R = 10\text{V}$                                |

### Suggested Solder Pad Layout



## RB421D

### ●Electrical characteristic curves (Ta = 25°C)




Fig. 1 Forward characteristics




Fig. 2 Reverse characteristics




Fig. 3 Capacitance between terminals characteristics




Fig. 4 Derating curve  
(mounting on glass epoxy PCBs)