


DATA SHEET



1N4531; 1N4532 High-speed diodes

Product specification
Supersedes data of April 1996

1996 Sep 03

High-speed diodes

1N4531; 1N4532

FEATURES


- Hermetically sealed leaded glass SOD68 (DO-34) package
- High switching speed: max. 4 ns
- Continuous reverse voltage: max. 75 V
- Repetitive peak reverse voltage: max. 75 V
- Repetitive peak forward current: max. 450 mA.

APPLICATIONS

- High-speed switching
- Protection diodes in reed relays.

DESCRIPTION

The 1N4531, 1N4532 are high-speed switching diodes fabricated in planar technology, and encapsulated in hermetically sealed leaded glass SOD68 (DO-34) packages.



The diodes are type branded.

Fig.1 Simplified outline (SOD68; DO-34) and symbol.

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{RRM}	repetitive peak reverse voltage		—	75	V
V_R	continuous reverse voltage		—	75	V
I_F	continuous forward current	see Fig.2	—	200	mA
I_{FRM}	repetitive peak forward current		—	450	mA
I_{FSM}	non-repetitive peak forward current	square wave; $T_j = 25\text{ °C}$ prior to surge; see Fig.4			
		$t = 1\text{ }\mu\text{s}$	—	4	A
		$t = 1\text{ ms}$	—	1	A
		$t = 1\text{ s}$	—	0.5	A
P_{tot}	total power dissipation	$T_{amb} = 25\text{ °C}$	—	500	mW
T_{stg}	storage temperature		−65	+200	°C
T_j	junction temperature		—	200	°C

High-speed diodes

1N4531; 1N4532

ELECTRICAL CHARACTERISTICS

$T_j = 25\text{ }^{\circ}\text{C}$; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_F	forward voltage	$I_F = 10\text{ mA}$; see Fig.3	—	1000	mV
I_R	reverse current	see Fig.5			
	IN4531	$V_R = 20\text{ V}$	—	25	nA
		$V_R = 20\text{ V}$; $T_j = 150\text{ }^{\circ}\text{C}$	—	50	μA
	IN4532	$V_R = 50\text{ V}$	—	100	nA
		$V_R = 50\text{ V}$; $T_j = 150\text{ }^{\circ}\text{C}$	—	100	μA
C_d	diode capacitance	$f = 1\text{ MHz}$; $V_R = 0$; see Fig.6			
	IN4531		—	4	pF
	IN4532		—	2	pF
t_{rr}	reverse recovery time	when switched from $I_F = 10\text{ mA}$ to $I_R = 60\text{ mA}$; $R_L = 100\text{ }\Omega$;			
	IN4531	measured at $I_R = 1\text{ mA}$; see Fig.7	—	4	ns
	IN4532		—	2	ns
	reverse recovery time	when switched from $I_F = 10\text{ mA}$ to $I_R = 10\text{ mA}$; $R_L = 100\text{ }\Omega$;			
	IN4532	measured at $I_R = 1\text{ mA}$; see Fig.7	—	4	ns
V_{fr}	forward recovery voltage	when switched from $I_F = 100\text{ mA}$;			
		$t_r \leq 30\text{ ns}$; see Fig.8	—	3	V

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j-tp}$	thermal resistance from junction to tie-point	lead length 5 mm	120	K/W
$R_{th\ j-a}$	thermal resistance from junction to ambient	lead length 5 mm; note 1	350	K/W




Note

1. Device mounted on a printed circuit-board without metallization pad.

High-speed diodes


1N4531; 1N4532

GRAPHICAL DATA




High-speed diodes

1N4531; 1N4532



$V_R = 50\text{ V}$
Solid line; maximum values.
Dotted line; typical values.

Fig.5 Reverse current as a function of junction temperature.





$f = 1\text{ MHz}; T_j = 25\text{ }^{\circ}C$.

Fig.6 Diode capacitance as a function of reverse voltage; typical values.

High-speed diodes


1N4531; 1N4532



High-speed diodes

1N4531; 1N4532

PACKAGE OUTLINE



DEFINITIONS

Data Sheet Status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.