


# DATA SHEET



## **BGY587**

550 MHz, 22 dB gain push-pull  
amplifier

Product specification  
Supersedes data of 1994 Feb 07

2001 Nov 27

550 MHz, 22 dB gain push-pull amplifier

BGY587

FEATURES

- Excellent linearity
- Extremely low noise
  - Silicon nitride passivation
  - Rugged construction
  - TiPtAu metallized crystals ensure optimal reliability.

APPLICATIONS


- CATV systems operating in the 40 to 550 MHz frequency range.

DESCRIPTION

Hybrid amplifier module in a SOT115J package operating with a voltage supply of 24 V (DC). The BGY587 is intended for use as a final amplifier.

PINNING - SOT115J

| PIN  | DESCRIPTION     |
|------|-----------------|
| 1    | input           |
| 2, 3 | common          |
| 5    | +V <sub>B</sub> |
| 7, 8 | common          |
| 9    | output          |



QUICK REFERENCE DATA

| SYMBOL           | PARAMETER                      | CONDITIONS            | MIN. | TYP. | MAX. | UNIT |
|------------------|--------------------------------|-----------------------|------|------|------|------|
| G <sub>p</sub>   | power gain                     | f = 50 MHz            | 21.5 | —    | 22.5 | dB   |
|                  |                                | f = 550 MHz           | 22   | —    | —    | dB   |
| I <sub>tot</sub> | total current consumption (DC) | V <sub>B</sub> = 24 V | —    | 220  | 240  | mA   |

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

| SYMBOL           | PARAMETER                           | MIN. | MAX. | UNIT |
|------------------|-------------------------------------|------|------|------|
| V <sub>i</sub>   | RF input voltage                    | —    | 65   | dBmV |
| T <sub>stg</sub> | storage temperature                 | −40  | +100 | °C   |
| T <sub>mb</sub>  | operating mounting base temperature | −20  | +100 | °C   |

## 550 MHz, 22 dB gain push-pull amplifier

BGY587

## CHARACTERISTICS

Bandwidth 40 to 550 MHz;  $V_B = 24$  V;  $T_{mb} = 30$  °C;  $Z_S = Z_L = 75$   $\Omega$ .

| SYMBOL    | PARAMETER                         | CONDITIONS                                                      | MIN. | TYP. | MAX.      | UNIT |
|-----------|-----------------------------------|-----------------------------------------------------------------|------|------|-----------|------|
| $G_p$     | power gain                        | $f = 50$ MHz                                                    | 21.5 | –    | 22.5      | dB   |
|           |                                   | $f = 550$ MHz                                                   | 22   | –    | –         | dB   |
| SL        | slope cable equivalent            | $f = 40$ to 550 MHz                                             | 0.2  | –    | 1.5       | dB   |
| FL        | flatness of frequency response    | $f = 40$ to 550 MHz                                             | –    | –    | $\pm 0.2$ | dB   |
| $S_{11}$  | input return losses               | $f = 40$ to 80 MHz                                              | 20   | –    | –         | dB   |
|           |                                   | $f = 80$ to 160 MHz                                             | 19   | –    | –         | dB   |
|           |                                   | $f = 160$ to 550 MHz                                            | 18   | –    | –         | dB   |
| $S_{22}$  | output return losses              | $f = 40$ to 80 MHz                                              | 20   | –    | –         | dB   |
|           |                                   | $f = 80$ to 160 MHz                                             | 19   | –    | –         | dB   |
|           |                                   | $f = 160$ to 550 MHz                                            | 18   | –    | –         | dB   |
| $S_{21}$  | phase response                    | $f = 50$ MHz                                                    | +135 | –    | +225      | deg  |
| CTB       | composite triple beat             | 77 channels flat;<br>$V_o = 44$ dBmV;<br>measured at 547.25 MHz | –    | –    | –57       | dB   |
| $X_{mod}$ | cross modulation                  | 77 channels flat;<br>$V_o = 44$ dBmV;<br>measured at 55.25 MHz  | –    | –    | –58       | dB   |
| CSO       | composite second order distortion | 77 channels flat;<br>$V_o = 44$ dBmV;<br>measured at 548.5 MHz  | –    | –    | –54       | dB   |
| $d_2$     | second order distortion           | note 1                                                          | –    | –    | –66       | dB   |
| $V_o$     | output voltage                    | $d_{im} = -60$ dB; note 2                                       | 61   | –    | –         | dBmV |
| NF        | noise figure                      | $f = 550$ MHz                                                   | –    | –    | 7         | dB   |
| $I_{tot}$ | total current consumption (DC)    | note 3                                                          | –    | 220  | 240       | mA   |

## Notes

- $f_p = 55.25$  MHz;  $V_p = 44$  dBmV;  
 $f_q = 493.25$  MHz;  $V_q = 44$  dBmV;  
measured at  $f_p + f_q = 548.5$  MHz.
- Measured according to DIN45004B:  
 $f_p = 540.25$  MHz;  $V_p = V_o$ ;  
 $f_q = 547.25$  MHz;  $V_q = V_o - 6$  dB;  
 $f_r = 549.25$  MHz;  $V_r = V_o - 6$  dB;  
measured at  $f_p + f_q - f_r = 538.25$  MHz.
- The module normally operate at  $V_B = 24$  V, but is able to withstand supply transients up to 30 V.


550 MHz, 22 dB gain push-pull amplifier

BGY587

PACKAGE OUTLINE

Rectangular single-ended package; aluminium flange; 2 vertical mounting holes;  
2 x 6-32 UNC and 2 extra horizontal mounting holes; 7 gold-plated in-line leads

SOT115J



DIMENSIONS (mm are the original dimensions)

| UNIT | A<br>max. | A <sub>2</sub><br>max. | b            | c    | D<br>max. | d<br>max. | E<br>max. | e    | e <sub>1</sub> | F    | L<br>min. | p            | Q<br>max. | q    | q <sub>1</sub> | q <sub>2</sub> | S   | U <sub>1</sub><br>max. | U <sub>2</sub> | W           | w    | y   | Z<br>max. |
|------|-----------|------------------------|--------------|------|-----------|-----------|-----------|------|----------------|------|-----------|--------------|-----------|------|----------------|----------------|-----|------------------------|----------------|-------------|------|-----|-----------|
| mm   | 20.8      | 9.1                    | 0.51<br>0.38 | 0.25 | 27.2      | 2.54      | 13.75     | 2.54 | 5.08           | 12.7 | 8.8       | 4.15<br>3.85 | 2.4       | 38.1 | 25.4           | 10.2           | 4.2 | 44.75                  | 8              | 6-32<br>UNC | 0.25 | 0.1 | 3.8       |

| OUTLINE<br>VERSION | REFERENCES |       |      |  | EUROPEAN<br>PROJECTION                                                                | ISSUE DATE |
|--------------------|------------|-------|------|--|---------------------------------------------------------------------------------------|------------|
|                    | IEC        | JEDEC | EIAJ |  |                                                                                       |            |
| SOT115J            |            |       |      |  |  | 99-02-06   |

## 550 MHz, 22 dB gain push-pull amplifier

BGY587

## DATA SHEET STATUS

| DATA SHEET STATUS <sup>(1)</sup> | PRODUCT STATUS <sup>(2)</sup> | DEFINITIONS                                                                                                                                                                                                                                                                                                            |
|----------------------------------|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Objective data                   | Development                   | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.                                                                                                                            |
| Preliminary data                 | Qualification                 | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.                                     |
| Product data                     | Production                    | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Changes will be communicated according to the Customer Product/Process Change Notification (CPCN) procedure SNW-SQ-650A. |

## Notes

1. Please consult the most recently issued data sheet before initiating or completing a design.
2. The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

## DEFINITIONS

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## DISCLAIMERS

**Life support applications** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

## CAUTION

This product is supplied in anti-static packing to prevent damage caused by electrostatic discharge during transport and handling. For further information, refer to Philips specs.: SNW-EQ-608, SNW-FQ-302A, and SNW-FQ-302B.

---

550 MHz, 22 dB gain push-pull amplifier

BGY587

---

**NOTES**

---

550 MHz, 22 dB gain push-pull amplifier

BGY587

---

**NOTES**

# ***Philips Semiconductors – a worldwide company***

## **Contact information**

For additional information please visit <http://www.semiconductors.philips.com>. Fax: **+31 40 27 24825**

For sales offices addresses send e-mail to: [sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com).

© Koninklijke Philips Electronics N.V. 2001

SCA73

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

613518/03/pp8

Date of release: 2001 Nov 27

Document order number: 9397 750 08966

*Let's make things better.*

**Philips  
Semiconductors**



**PHILIPS**