


DATA SHEET



PRL4001; PRL4002 **Rectifiers**

Product specification
Supersedes data of November 1993

1996 Jun 10

Rectifiers

PRLL4001; PRLL4002

FEATURES


- Glass passivated
- High maximum operating temperature
- Low leakage current
- Excellent stability
- Shipped in 8 mm embossed tape
- Smallest surface mount rectifier outline.

DESCRIPTION

Cavity free cylindrical glass package through Implotec™⁽¹⁾ technology.

(1) Implotec is a trademark of Philips.

This package is hermetically sealed and fatigue free as coefficients of expansion of all used parts are matched.



LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{RRM}	repetitive peak reverse voltage				
	PRLL4001		—	50	V
	PRLL4002		—	100	V
V_R	continuous reverse voltage				
	PRLL4001		—	50	V
	PRLL4002		—	100	V
$I_{F(AV)}$	average forward current	averaged over any 20 ms period; $T_{tp} = 105\text{ °C}$	—	1.60	A
		averaged over any 20 ms period; $T_{amb} = 65\text{ °C}$; see Fig.2	—	0.68	A
I_{FRM}	repetitive peak forward current		—	10	A
I_{FSM}	non-repetitive peak forward current	half sinewave; 60 Hz	—	20	A
T_{stg}	storage temperature		−65	+175	°C
T_j	junction temperature		−65	+175	°C

Rectifiers

PRLL4001; PRLL4002

ELECTRICAL CHARACTERISTICS

$T_j = 25\text{ }^{\circ}\text{C}$; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MAX.	UNIT
V_F	forward voltage	$I_F = 1\text{ A}$; see Fig.3	1.1	V
$V_{F(AV)}$	full-cycle average forward voltage	$I_{F(AV)} = 1\text{ A}$	0.8	V
I_R	reverse current	$V_R = V_{Rmax}$	10	μA
		$V_R = V_{Rmax}$; $T_{amb} = 100\text{ }^{\circ}\text{C}$	50	μA
$I_{R(AV)}$	full-cycle average reverse current	$V_R = V_{RRMmax}$; $T_{amb} = 75\text{ }^{\circ}\text{C}$	30	μA

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j-tp}$	thermal resistance from junction to tie-point		30	K/W
$R_{th\ j-a}$	thermal resistance from junction to ambient	note 1	150	K/W




Note

1. Device mounted on epoxy-glass printed-circuit board, 1.5 mm thick; thickness of copper $\geq 40\text{ }\mu\text{m}$, see Fig.4.
For more information please refer to the "General Part of associated Handbook".

Rectifiers

PRLL4001; PRLL4002


GRAPHICAL DATA



Rectifiers

PRLL4001; PRLL4002

PACKAGE OUTLINE



DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.