

Silicon Variable Capacitance Diode for Electronic Tuning of BS and CS Tuners

Description

The 1T379 is a variable capacitance diode designed for the electronic tuning of BS and CS tuners, and it has a super miniature package.


Features

- Super miniature package
- Small series resistance 1.50 Ω Max. (f=470 MHz)
- Large capacitance ratio 12.0 Typ. (C_1/C_{25})
- Small capacitance 0.60 pF Max. ($V_R=25$ V)

Structure

Silicon epitaxial planar-type diode

M-235



Absolute Maximum Ratings ($T_a=25$ °C)





- Reverse voltage V_R 30 V
- Maximum reverse voltage V_{RM} 35 V
($R_L \geq 10$ k Ω)
- Operating temperature T_{opr} -20 to +75 °C
- Storage temperature T_{stg} -65 to +150 °C

Electrical Characteristics


($T_a=25$ °C)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Reverse current	I_R	$V_R=25$ V			10	nA
Reverse voltage	V_R	$I_R=1$ μ A	30			V
Diode capacitance	C_1	$V_R=1$ V, f=1 MHz	6.0		7.2	pF
	C_{25}	$V_R=25$ V, f=1 MHz	0.5		0.6	pF
Capacitance ratio	C_1/C_{25}	f=1 MHz	10.0	12.0		
Series resistance	r_s	$V_R=5$ V, f=470 MHz			1.50	Ω
Capacitance deviation in a matching group	ΔC	$V_R=1$ to 25 V, f=1 MHz			6	%


Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.




Reverse voltage vs. Ambient temperature



Reverse current vs. Ambient temperature




Reverse current vs. Reverse voltage



Package Outline Unit : mm

M-235




NOTE: Dimension "*" does not include mold protrusion.

SONY CODE	M-235
EIAJ CODE	_____
JEDEC CODE	_____

PACKAGE WEIGHT	0.1g
----------------	------

Marking



Notes
1) B: Lot No. (Year and Month of manufacture)
Year; Last one digit
Month; A, B, C (for Oct. to Dec.)
1 to 9 (for Jan. to Sept.)