

TOSHIBA TRANSISTOR TOSHIBA (DISCRETE/OPTO)  
 SILICON PNP EPITAXIAL TYPE (PCT PROCESS)

**2SA968B**

T 33-19


POWER AMPLIFIER APPLICATIONS.  
 DRIVER STAGE AMPLIFIER APPLICATIONS.

## FEATURES:

- High Transition Frequency;  $f_T=100\text{MHz}$  (Typ.)
- Complementary to 2SC2238B

MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$ )

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage	2SA968B	$V_{CB0}$	-200	V
Collector-Emitter Voltage	2SA968B	$V_{CE0}$	-200	V
Emitter-Base Voltage		$V_{EB0}$	-5	V
Collector Current		$I_C$	-1.5	A
Emitter Current		$I_E$	1.5	A
Collector Power Dissipation ( $T_c=25^\circ\text{C}$ )		$P_C$	25	W
Junction Temperature		$T_j$	150	$^\circ\text{C}$
Storage Temperature Range		$T_{stg}$	-55~150	$^\circ\text{C}$



Mounting Kit No. AC75  
 Weight : 1.9g

ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$ )

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		$I_{CB0}$	$V_{CB}=-160\text{V}, I_E=0$	-	-	-1.0	$\mu\text{A}$
Emitter Cut-off Current		$I_{EB0}$	$V_{EB}=-5\text{V}, I_C=0$	-	-	-1.0	$\mu\text{A}$
Collector-Emitter Breakdown Voltage	2SA968B	$V_{(BR)CE0}$	$I_C=-10\text{mA}, I_B=0$	-200	-	-	V
Emitter-Base Breakdown Voltage		$V_{(BR)EB0}$	$I_E=-1\text{mA}, I_C=0$	-5	-	-	V
DC Current Gain		$h_{FE}$ (Note)	$V_{CE}=-5\text{V}, I_C=-100\text{mA}$	70	-	240	
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	$I_C=-500\text{mA}, I_B=-50\text{mA}$	-	-	-1.5	V
Base-Emitter Voltage		$V_{BE}$	$V_{CE}=-5\text{V}, I_C=-500\text{mA}$	-	-	-1.0	V
Transition Frequency		$f_T$	$V_{CE}=-10\text{V}, I_C=-100\text{mA}$	-	100	-	MHz
Collector Output Capacitance		$C_{ob}$	$V_{CB}=-10\text{V}, I_E=0, f=1\text{MHz}$	-	30	-	pF

Note:  $h_{FE}$  Classification O: 70~140, Y: 120~240

TOSHIBA (DISCRETE/OPTO)

2SA968B

