

SIPMOS® Power-Transistor


Feature

- N-Channel
- Enhancement mode
- 175°C operating temperature
- Avalanche rated
- dv/dt rated


Product Summary

V_{DS}	100	V
$R_{DS(on)}$	180	mΩ
I_D	10.3	A


P-TO262-3-1




P-TO263-3-2



P-TO220-3-1



Type	Package	Ordering Code	Marking
SPP10N10	P-TO220-3-1	-	10N10
SPB10N10	P-TO263-3-2	-	10N10
SPI10N10	P-TO262-3-1	-	10N10



Maximum Ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_C=25^\circ\text{C}$ $T_C=100^\circ\text{C}$	I_D	10.3 -	A
Pulsed drain current $T_C=25^\circ\text{C}$	$I_{D \text{ puls}}$	41.2	
Avalanche energy, single pulse $I_D=10.3 \text{ A}$, $V_{DD}=25\text{V}$, $R_{GS}=25\Omega$	E_{AS}	60	mJ
Reverse diode dv/dt $I_S=10.3\text{A}$, $V_{DS}=80\text{V}$, $di/dt=200\text{A}/\mu\text{s}$, $T_{j\text{max}}=175^\circ\text{C}$	dv/dt	6	kV/ μs
Gate source voltage	V_{GS}	± 20	V
Power dissipation $T_C=25^\circ\text{C}$	P_{tot}	50	W
Operating and storage temperature	T_j, T_{stg}	-55... +175	$^\circ\text{C}$
IEC climatic category; DIN IEC 68-1		55/175/56	

Thermal Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Characteristics					
Thermal resistance, junction - case	R_{thJC}	-	-	3	K/W
Thermal resistance, junction - ambient, leaded	R_{thJA}	-	-	100	
SMD version, device on PCB:	R_{thJA}				
@ min. footprint		-	-	75	
@ 6 cm ² cooling area ¹⁾		-	-	50	

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Static Characteristics					
Drain-source breakdown voltage $V_{GS}=0V, I_D=1mA$	$V_{(BR)DSS}$	100	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D = 21 \mu A$	$V_{GS(th)}$	2.1	3	4	
Zero gate voltage drain current $V_{DS}=100V, V_{GS}=0V, T_j=25^{\circ}C$ $V_{DS}=100V, V_{GS}=0V, T_j=125^{\circ}C$	I_{DSS}	- -	0.01 1	1 100	μA
Gate-source leakage current $V_{GS}=20V, V_{DS}=0V$	I_{GSS}	-	1	100	
Drain-source on-state resistance $V_{GS}=10V, I_D=-A$	$R_{DS(on)}$	-	tbd	180	$m\Omega$

¹Device on 40mm*40mm*1.5mm epoxy PCB FR4 with 6cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical without blown air.

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic Characteristics

Transconductance	g_{fs}	$V_{DS} \geq 2 \cdot I_D \cdot R_{DS(on)max}$, $I_D = -A$	tbd	tbd	-	S
Input capacitance	C_{iss}	$V_{GS}=0V$, $V_{DS}=25V$, $f=1MHz$	-	tbd	tbd	pF
Output capacitance	C_{oss}		-	tbd	tbd	
Reverse transfer capacitance	C_{rss}		-	tbd	tbd	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=50V$, $V_{GS}=10V$, $I_D=10.3A$, $R_G=28\Omega$	-	tbd	tbd	ns
Rise time	t_r		-	tbd	tbd	
Turn-off delay time	$t_{d(off)}$		-	tbd	tbd	
Fall time	t_f		-	tbd	tbd	

Gate Charge Characteristics

Gate to source charge	Q_{gs}	$V_{DD}=80V$, $I_D=10.3A$	-	tbd	tbd	nC
Gate to drain charge	Q_{gd}		-	tbd	tbd	
Gate charge total	Q_g	$V_{DD}=80V$, $I_D=10.3A$, $V_{GS}=0$ to $10V$	-	tbd	tbd	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD}=80V$, $I_D=10.3A$	-	tbd	-	V

Reverse Diode

Inverse diode continuous forward current	I_S	$T_C=25^\circ\text{C}$	-	-	10.3	A
Inverse diode direct current, pulsed	I_{SM}		-	-	41.2	
Inverse diode forward voltage	V_{SD}	$V_{GS}=0V$, $I_F=10.3A$	-	tbd	tbd	V
Reverse recovery time	t_{rr}	$V_R=50V$, $I_F=I_S$, $di_F/dt=100A/\mu s$	-	tbd	tbd	ns
Reverse recovery charge	Q_{rr}		-	tbd	tbd	nC

Published by
Infineon Technologies AG,
Bereichs Kommunikation
St.-Martin-Strasse 53,
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

Warnings

Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.