



Monolithic Dual Switching Diode Common Anode



BAW56LT1



CASE 318-08, STYLE12
SOT- 23 (TO-236AB)

MAXIMUM RATINGS (EACH DIODE)

Rating	Symbol	Value	Unit
Reverse Voltage	V_R	70	Vdc
Forward Current	I_F	200	mAdc
Peak Forward Surge Current	$I_{FM(surge)}$	500	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR- 5 Board (1) $T_A = 25^\circ\text{C}$	P_D	225	mW
Derate above 25°C		1.8	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	556	$^\circ\text{C/W}$
Total Device Dissipation Alumina Substrate, ⁽²⁾ $T_A = 25^\circ\text{C}$	P_D	300	mW
Derate above 25°C		2.4	mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	417	$^\circ\text{C/W}$
Junction and Storage Temperature	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

DEVICE MARKING

BAW56LT1 = A1

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (EACH DIODE)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Reverse Breakdown Voltage ($I_{(BR)} = 100 \mu\text{Adc}$)	$V_{(BR)}$	70	—	Vdc
Reverse Voltage Leakage Current ($V_R = 25 \text{ Vdc}, T_J = 150^\circ\text{C}$)	I_R	—	30	μAdc
($V_R = 70 \text{ Vdc}$)		—	2.5	
($V_R = 70 \text{ Vdc}, T_J = 150^\circ\text{C}$)		—	50	
Diode Capacitance ($V_R = 0, f = 1.0 \text{ MHz}$)	C_D	—	2.0	pF
Forward Voltage ($I_F = 1.0 \text{ mAdc}$)	V_F	—	715	mVdc
($I_F = 10 \text{ mAdc}$)		—	855	
($I_F = 50 \text{ mAdc}$)		—	1000	
($I_F = 150 \text{ mAdc}$)		—	1250	
Reverse Recovery Time ($I_F = I_R = 10 \text{ mAdc}, I_{R(REC)} = 1.0 \text{ mAdc}$) (Figure 1) $R_L = 100\Omega$	t_{rr}	—	6.0	ns

1. FR-5 = $1.0 \times 0.75 \times 0.062 \text{ in.}$

2. Alumina = $0.4 \times 0.3 \times 0.024 \text{ in.}$ 99.5% alumina.

- Notes: 1. A 2.0 k Ω variable resistor adjusted for a Forward Current (I_F) of 10mA.
2. Input pulse is adjusted so $I_{R(\text{peak})}$ is equal to 10mA.
3. $t_p \gg t_r$

Figure 1. Recovery Time Equivalent Test Circuit

The graph shows the forward current I_F (mA) on a logarithmic y-axis (0.1 to 100) versus forward voltage V_F (V) on a linear x-axis (0.2 to 1.2). Three curves are plotted for different ambient temperatures T_A :

- $T_A = 85^\circ\text{C}$ (Leftmost curve)
- $T_A = 25^\circ\text{C}$ (Middle curve)
- $T_A = -40^\circ\text{C}$ (Rightmost curve)

Approximate data points extracted from the graph:

V_F (V)	I_F (mA) at 85°C	I_F (mA) at 25°C	I_F (mA) at -40°C
0.4	0.1	-	-
0.5	1.0	0.1	-
0.6	10.0	1.0	0.1
0.7	30.0	10.0	1.0
0.8	60.0	30.0	3.0
0.9	80.0	60.0	10.0
1.0	90.0	80.0	30.0

 V_F , FORWARD VOLTAGE (VOLTS)

Figure 2. Forward Voltage


 V_R , REVERSE VOLTAGE (VOLTS)

Figure 3. Leakage Current




Figure 4. Capacitance