


SOT89 NPN SILICON PLANAR MEDIUM POWER TRANSISTORS

ISSUE 3 – FEBRUARY 1996

BSR41 BSR43

COMPLEMENTARY TYPES – BSR43 - BSR33
BSR41 - BSR31

PARTMARKING DETAIL – BSR43 - AR4
BSR41 - AR2



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	BSR41	BSR43	UNIT
Collector-Base Voltage	V_{CBO}	70	90	V
Collector-Emitter Voltage	V_{CEO}	60	80	V
Emitter-Base Voltage	V_{EBO}	5		V
Peak Pulse Current	I_{CM}	2		A
Continuous Collector Current	I_C	1		A
Base Current	I_B	100		mA
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{TOT}	1		W
Operating and Storage Temperature Range	$T_J:T_{stg}$	-65 to +150		$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage BSR43 BSR41	$V_{(BR)CBO}$	90 70		V	$I_C=100\mu A$
Collector-Emitter Breakdown Voltage BSR43 BSR41	$V_{(BR)CEO}$	80 60		V	$I_C=10mA$ *
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5		V	$I_E=10\mu A$
Collector Cut-Off Current	I_{CBO}		100 50	nA μA	$V_{CB}=60V$ $V_{CB}=60V, T_{amb} = 125^{\circ}C$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		0.25 0.5	V V	$I_C = 150mA, I_B = 15mA$ $I_C = 500mA, I_B = 50mA$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		1.0 1.2	V V	$I_C = 150mA, I_B = 15mA$ $I_C = 500mA, I_B = 50mA$
Static Forward Current Transfer Ratio	h_{FE}	30 100 50	300		$I_C = 100\mu A, V_{CE} = 5V$ $I_C = 100mA, V_{CE} = 5V$ $I_C = 500mA, V_{CE} = 5V$
Collector Capacitance	C_c		12	pF	$V_{CB} = 10V, f = 1MHz$
Emitter Capacitance	C_e		90	pF	$V_{EB} = 0.5V, f = 1MHz$
Transition Frequency	f_T	100		MHz	$I_C = 50mA, V_{CE} = 10V$ $f = 35MHz$
Turn-On Time	T_{on}		250	ns	$V_{CC} = 20V, I_C = 100mA$ $I_{B1} = I_{B2} = 5mA$
Turn-Off Time	T_{off}		1000	ns	

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$
For typical characteristics graphs see FMMT493 datasheet.