

SD703C..L SERIES

FAST RECOVERY DIODES

Hockey Puk Version


Features

- High power FAST recovery diode series
- 2.0 to 3.0 μ s recovery time
- High voltage ratings up to 2500V
- High current capability
- Optimized turn on and turn off characteristics
- Low forward recovery
- Fast and soft reverse recovery
- Press-puk encapsulation
- Case style conform to JEDEC DO-200AB (B-PUK)
- Maximum junction temperature 150°C

Typical Applications

- Snubber diode for GTO
- High voltage free-wheeling diode
- Fast recovery rectifier applications

700A
790A



case style DO-200AB (B-PUK)

Major Ratings and Characteristics

Parameters	SD703C..L		Units
	S20	S30	
$I_{F(AV)}$	700	790	A
@ T_{hs}	55	55	°C
$I_{F(RMS)}$	1320	1470	A
I_{FSM} @ 50Hz	9300	9600	A
@ 60Hz	9730	10050	A
V_{RRM} range	1200 to 2500	1200 to 2500	V
t_{rr}	2.0	3.0	μ s
@ T_J	25	25	°C
T_J	- 40 to 150		°C

SD703C..L Series

Bulletin I2075 rev.D 04/00

International
IOR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings


Type number	Voltage Code	V_{RRM} , maximum repetitive peak reverse voltage V	V_{RSM} , maximum non-repetitive peak rev. voltage V	I_{RRM} max. @ $T_J = T_J$ max. mA
SD703C..L	12	1200	1300	50
	16	1600	1700	
	20	2000	2100	
	25	2500	2600	

Forward Conduction

Parameter		SD703C..L		Units	Conditions
		S20	S30		
$I_{F(AV)}$	Max. average forward current @ case temperature	700 (365) 55 (85)	790 (400) 55 (85)	A °C	180° conduction, half sine wave Double side (single side) cooled
$I_{F(RMS)}$	Max. RMS forward current	1320	1470	A	@ 25°C heatsink temperature double side cooled
I_{FSM}	Max. peak, one-cycle forward, non-repetitive surge current	9300 9730 7820 8190	9600 10050 8070 8450	A	t = 10ms t = 8.3ms t = 10ms t = 8.3ms No voltage reapplied 100% V_{RRM} reapplied Sinusoidal half wave, Initial $T_J = T_J$ max.
I^2t	Maximum I^2t for fusing	432 395 306 279	460 420 326 297	KA²s	t = 10ms t = 8.3ms t = 10ms t = 8.3ms No voltage reapplied 100% V_{RRM} reapplied
$I^2\sqrt{t}$	Maximum $I^2\sqrt{t}$ for fusing	4320	4600	KA²√s	t = 0.1 to 10ms, no voltage reapplied
$V_{F(TO)1}$	Low level value of threshold voltage	1.00	0.95	V	(16.7% x π x $I_{F(AV)} < I < \pi$ x $I_{F(AV)}$), $T_J = T_J$ max.
$V_{F(TO)2}$	High level value of threshold voltage	1.11	1.05		($I > \pi$ x $I_{F(AV)}$), $T_J = T_J$ max.
r_{f1}	Low level value of forward slope resistance	0.80	0.60	mΩ	(16.7% x π x $I_{F(AV)} < I < \pi$ x $I_{F(AV)}$), $T_J = T_J$ max.
r_{f2}	High level value of forward slope resistance	0.76	0.56		($I > \pi$ x $I_{F(AV)}$), $T_J = T_J$ max.
V_{FM}	Max. forward voltage drop	2.20	1.85	V	$I_{pk} = 1500A$, $T_J = T_J$ max, $t_p = 10ms$ sinusoidal wave

Recovery Characteristics

Code	$T_J = 25^\circ C$ typical t_{rr} @ 25% I_{RRM} (μs)	Test conditions			Max. values @ $T_J = 150^\circ C$		
		I_{pk} Square Pulse (A)	di/dt (A/μs)	V_r (V)	t_{rr} @ 25% I_{RRM} (μs)	Q_{rr} (μC)	I_{rr} (A)
S20	2.0	1000	50	-50	3.5	240	110
S30	3.0	1000	50	-50	5.0	380	130



Thermal and Mechanical Specifications

Parameter		SD703C..L		Units	Conditions
		S20	S30		
T _J	Max. junction operating temperature range	-40 to 150		°C	
T _{stg}	Max. storage temperature range	-40 to 150			
R _{thJ-hs}	Max. thermal resistance, case junction to heatsink	0.092 0.046		K/W	DCoperation single side cooled DCoperation double side cooled
F	Mounting force, ± 10%	9800 (1000)		N (Kg)	
wt	Approximate weight	250		g	
Case style		DO-200AB (B-PUK)			See Outline Table

ΔR_{thJ-hs} Conduction

(The following table shows the increment of thermal resistance R_{thJ-hs} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction		Rectangular conduction		Units	Conditions
	Single Side	Double Side	Single Side	Double Side		
180°	0.011	0.011	0.008	0.008	K/W	$T_J = T_{J \text{ max.}}$
120°	0.013	0.014	0.013	0.013		
90°	0.017	0.017	0.018	0.018		
60°	0.024	0.025	0.026	0.026		
30°	0.043	0.043	0.043	0.044		

Ordering Information Table

Device Code

SD	70	3	C	25	S20	L
①	②	③	④	⑤	⑥	⑦

- 1** - Diode
- 2** - Essential part number
- 3** - 3 = Fast recovery
- 4** - C = Ceramic Puk
- 5** - Voltage code: Code x 100 = V_{RRM} (See Voltage Ratings table)
- 6** - t_{rr} code
- 7** - L = Puk Case DO-200AB (B-PUK)

SD703C..L Series

Bulletin I2075 rev.D 04/00

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - Current Ratings Characteristics




Fig. 6 - Current Ratings Characteristics




Fig. 7 - Current Ratings Characteristics




Fig. 8 - Current Ratings Characteristics

SD703C..L Series

Bulletin I2075 rev. D 04/00

International
IOR Rectifier




Fig. 9 - Forward Power Loss Characteristics




Fig. 10 - Forward Power Loss Characteristics




Fig. 11 - Forward Power Loss Characteristics




Fig. 12 - Forward Power Loss Characteristics




Fig. 13 - Maximum Non-repetitive Surge Current
Single and Double Side Cooled




Fig. 14 - Maximum Non-repetitive Surge Current
Single and Double Side Cooled




Fig. 15 - Maximum Non-repetitive Surge Current Single and Double Side Cooled




Fig. 16 - Maximum Non-repetitive Surge Current Single and Double Side Cooled




Fig. 17 - Forward Voltage Drop Characteristics




Fig. 18 - Forward Voltage Drop Characteristics




Fig. 19 - Thermal Impedance Z_{thJ-hs} Characteristic

SD703C..L Series

Bulletin I2075 rev. D 04/00

International
IR Rectifier




Fig. 20 - Typical Forward Recovery Characteristics




Fig. 21 - Typical Forward Recovery Characteristics




Fig. 22 - Recovery Time Characteristics




Fig. 23 - Recovery Charge Characteristics




Fig. 24 - Recovery Current Characteristics




Fig. 25 - Recovery Time Characteristics




Fig. 26 - Recovery Charge Characteristics




Fig. 27 - Recovery Current Characteristics




Fig. 28 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 29 - Frequency Characteristics




Fig. 30 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 31 - Frequency Characteristics




Fig. 32 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 33 - Frequency Characteristics

SD703C..L Series

Bulletin I2075 rev. D 04/00

International
IRF Rectifier




Fig. 34 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 35 - Frequency Characteristics




Fig. 36 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 37 - Frequency Characteristics




Fig. 38 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 39 - Frequency Characteristics