

SB1620CT THRU SB16100CT

16 AMPERE SCHOTTKY BARRIER RECTIFIERS

VOLTAGE - 20 to 100 Volts CURRENT - 16.0 Amperes

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency
- Low forward voltage, high current capability
- High surge capacity
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

MECHANICAL DATA

Case: TO-220AB molded plastic


Terminals: Lead, solderable per MIL-STD-202, Method 208

Polarity: As marked

Mounting Position: Any

Weight: 0.08 ounces, 2.24 grams

TO-220AB



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half wave 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	SB1620CT	SB1630CT	SB1640CT	SB1650CT	SB1660CT	SB1680CT	SB16100CT	UNIT
Maximum Recurrent Peak Reverse Voltage	20	30	40	50	60	80	100	V
Maximum RMS Voltage	14	21	26	35	42	56	80	V
Maximum DC Blocking Voltage	20	30	40	50	60	80	100	V
Maximum Average Forward Rectified Current at T _C =90 ºJ	16.0							A
Peak Forward Surge Current, 8.3ms single half sine wave superimposed on rated load(JEDEC method)	150							A
Maximum Forward Voltage at 8.0A per element	0.55		0.75		0.85			V
Maximum DC Reverse Current at Rated T _C =25 ºJ	0.5							mA
DC Blocking Voltage per element T _C =100 ºJ	100							
Typical Thermal Resistance Note R £KJA	60							ºC/W
Operating and Storage Temperature Range T _J	-50 TO +125							ºC

NOTES:

Thermal Resistance Junction to Ambient

RATING AND CHARACTERISTIC CURVES

SB1620CT THRU SB16100CT




Fig. 1-FORWARD CURRENT DERATING CURVE




Fig. 2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC




Fig. 3-TYPICAL REVERSE CHARACTERISTICS




Fig. 4-MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig. 5-TYPICAL JUNCTION CAPACITANCE