



MILITARY DATA SHEET

MN54F534-X REV 1A0

Original Creation Date: 05/06/96
 Last Update Date: 07/30/96
 Last Major Revision Date: 05/06/96

OCTAL D-TYPE FLIP-FLOP WITH TRI-STATE OUTPUTS

General Description

The F534 is a high speed, low-power octal D-type flip-flop featuring separate D-type inputs for each flip-flop and TRI-STATE outputs for bus-oriented applications. A buffered Clock (CP) and Output Enable (\overline{OE}) are common to all flip-flops. The F534 is the same as the F374 except that the outputs are inverted.

Industry Part Number

54F534

NS Part Numbers

54F534DMQB
 54F534FMQB
 54F534LMQB

Prime Die

M534

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- Edge-Triggered D-type inputs
- Buffered Positive Edge - Triggered Clock
- 3-State Output for Bus - Oriented Applications

(Absolute Maximum Ratings)

(Note 1)

Storage Temperature	-65C to +150C
Ambient Temperature under Bias	-55C to +125C
Junction Temperature under Bias	-55C to +175C
Vcc Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30mA to +5.0mA
Voltage Applied to Output in HIGH State (with Vcc=0V)	
Standard Output	-0.5V to Vcc
TRI-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated Iol(mA)
ESD Last Passing Voltage (Min)	4000V

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	
Commercial	0 C to +70 C
Military	-55 C to +125 C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
DC: VCC 4.5V to 5.5V, Temp range: -55C to 125C

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	Input High Current	VCC=5.5V, VM=2.7V, VINH=5.5V	1, 3	INPUTS		20	uA	1, 2, 3
IBVI	Input High Current	VCC=5.5V, VM=7.0V, VINH=5.5V	1, 3	INPUTS		100	uA	1, 2, 3
IIL	Input LOW Current	VCC=5.5V, VM=0.5V, VINH=5.5V	1, 3	INPUTS		-0.6	mA	1, 2, 3
VOL	Output LOW Voltage	VCC=4.5V, VIL=0.8V, IOL=20mA, VIH=2.0V, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS		0.5	V	1, 2, 3
VOH	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH=-1.0mA	1, 3	OUTPUTS	2.5		V	1, 2, 3
VOH3	Output HIGH Voltage	VCC=4.5V, VIL=0.8V, IOH3=-3.0mA, VINH=5.5V	1, 3	OUTPUTS	2.4		V	1, 2, 3
IOS	Short-Circuit Current	VCC=5.5V, VINH=5.5V, VM=0.0V, VINL=0.0V	1, 3	OUTPUTS	-60	-150	mA	1, 2, 3
VCD	Input Clamp Diode Voltage	VCC=4.5V, IM=-18mA, VINH=5.5V	1, 3	INPUTS		-1.2	V	1, 2, 3
ICCZ	Power Supply Current	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 3	VCC		86	mA	1, 2, 3
ICEX	Output HIGH Leakage Current	VCC=5.5V, VINH=5.5V, VINL=0.0V, VM=5.5V	1, 3	OUTPUTS		250	uA	1, 2, 3
IOZH	Output Leakage Current	VCC=5.5V, VM=2.7V, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS		50	uA	1, 2, 3
IOZL	Output Leakage Current	VCC=5.5V, VM=0.5V, VINH=5.5V, VINL=0.0V	1, 3	OUTPUTS		-50	uA	1, 2, 3

Electrical Characteristics

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)
 AC: CL=50pf, RL=500 OHMS, TR=2.5ns, TF=2.5ns SEE AC FIGS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpLH	Propagation Delay	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	CP to $\bar{O}n$	4.0	8.5	ns	9
			2, 4	CP to $\bar{O}n$	4.0	10.5	ns	10, 11
tpHL	Propagation Delay	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	CP to $\bar{O}n$	4.0	8.5	ns	9
			2, 4	CP to $\bar{O}n$	4.0	11.0	ns	10, 11
tpZH	Output Enable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	11.5	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	14.0	ns	10, 11
tpZL	Output Enable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	7.5	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	2.0	10.0	ns	10, 11
tpHZ	Output Disable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	7.0	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	8.0	ns	10, 11
tpLZ	Output Disable	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	5.5	ns	9
			2, 4	$\bar{O}E$ to $\bar{O}n$	1.5	7.5	ns	10, 11
ts(H)	Setup Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9, 10, 11
ts(L)	Setup Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9
			5	D to CP	2.5		ns	10, 11
th(H)	Hold Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9, 10, 11
th(L)	Hold Time	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C	5	D to CP	2.0		ns	9
			5	D to CP	2.5		ns	10, 11
tw(H)	Pulse Width	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C TR/TF=1.0ns	5	CP	7.0		ns	9, 10, 11
tw(L)	Pulse Width	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C TR/TF=1.0ns	5	CP	6.0		ns	9, 10, 11
fMAX	Maximum Clock Frequency	VCC=5.0V @ 25C, VCC=4.5V & 5.5V @ -55/125C TR/TF=1.0ns	5		100		MHZ	9
			5		60		MHZ	10, 11

(Continued)

- Note 1: Screen tested 100% on each device at -55 C, +25 C & +125 C temperature, Subgroups A1, 2, 3, 7 & 8.
- Note 2: Screen tested 100% on each device at +25 C temperature only, Subgroup A9.
- Note 3: Sample tested (Method 5005, Table 1) on each MFG. lot at +25 C, +125 C & -55 C temp., Subgroups A1, 2, 3, 7 & 8.
- Note 4: Sample Tested (Method 5005, Table 1) on each MFG. lot at +25 C Subgroup A9, & periodically at +125 C & -55 C temp., Subgroups 10 & 11.
- Note 5: Guaranteed but not tested. (DESIGN CHARACTERIZATION DATA)