

74HC1G14-Q100; 74HCT1G14-Q100

Inverting Schmitt trigger

Rev. 2 — 27 December 2012

Product data sheet

1. General description

74HC1G14-Q100 and 74HCT1G14-Q100 are high-speed Si-gate CMOS devices. They provide an inverting buffer function with Schmitt trigger action. These devices are capable of transforming slowly changing input signals into sharply defined, jitter-free output signals.

The HC device has CMOS input switching levels and supply voltage range 2 V to 6 V.

The HCT device has TTL input switching levels and supply voltage range 4.5 V to 5.5 V.

The standard output currents are half of those of the 74HC14-Q100 and 74HCT14-Q100.

This product has been qualified to the Automotive Electronics Council (AEC) standard Q100 (Grade 1) and is suitable for use in automotive applications.

2. Features and benefits

- Automotive product qualification in accordance with AEC-Q100 (Grade 1)
 - ◆ Specified from $-40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$ and from $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$
- Input levels:
 - ◆ For 74HC1G14-Q100: CMOS level
 - ◆ For 74HCT1G14-Q100: TTL level
- Symmetrical output impedance
- High noise immunity
- Low power dissipation
- Balanced propagation delays
- ESD protection:
 - ◆ MIL-STD-883, method 3015 exceeds 2000 V
 - ◆ HBM JESD22-A114F exceeds 2000 V
 - ◆ MM JESD22-A115-A exceeds 200 V ($C = 200\text{ pF}$, $R = 0\text{ }\Omega$)
- SOT353-1 and SOT753 package options

3. Applications

- Wave and pulse shapers
- Astable multivibrators
- Monostable multivibrators



4. Ordering information

Table 1. Ordering information

| Type number | Package | | | Version |
|-------------------------------------|-------------------|--------|---|----------|
| | Temperature range | Name | Description | |
| 74HC1G14GW-Q100 74HCT1G14GW-Q100 | -40 °C to +125 °C | TSSOP5 | plastic thin shrink small outline package; 5 leads; body width 1.25 mm | SOT353-1 |
| 74HC1G14GV-Q100 74HCT1G14GV-Q100 | -40 °C to +125 °C | SC-74A | plastic surface-mounted package; 5 leads | SOT753 |


5. Marking

Table 2. Marking codes

| Type number | Marking code ^[1] |
|------------------|-----------------------------|
| 74HC1G14GW-Q100 | HF |
| 74HCT1G14GW-Q100 | TF |
| 74HC1G14GV-Q100 | H14 |
| 74HCT1G14GV-Q100 | T14 |


[1] The pin 1 indicator is located on the lower left corner of the device, below the marking code.

6. Functional diagram




mna023

Fig 1. Logic symbol



mna024

Fig 2. IEC logic symbol




mna025

Fig 3. Logic diagram

7. Pinning information

7.1 Pinning

74HC1G14-Q100
74HCT1G14-Q100



aaa-004626

Fig 4. Pin configuration

7.2 Pin description

Table 3. Pin description

| Symbol | Pin | Description |
|-----------------|-----|----------------|
| n.c. | 1 | not connected |
| A | 2 | data input |
| GND | 3 | ground (0 V) |
| Y | 4 | data output |
| V _{CC} | 5 | supply voltage |

8. Functional description

Table 4. Function table

H = HIGH voltage level; L = LOW voltage level

| Input | Output |
|-------|--------|
| A | Y |
| L | H |
| H | L |

9. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V). [\[1\]](#)

| Symbol | Parameter | Conditions | Min | Max | Unit |
|------------------|-------------------------|---|-----------------------|-------|------|
| V _{CC} | supply voltage | | -0.5 | +7.0 | V |
| I _{IK} | input clamping current | V _I < -0.5 V or V _I > V _{CC} + 0.5 V | - | ±20 | mA |
| I _{OK} | output clamping current | V _O < -0.5 V or V _O > V _{CC} + 0.5 V | - | ±20 | mA |
| I _O | output current | -0.5 V < V _O < V _{CC} + 0.5 V | - | ±12.5 | mA |
| I _{CC} | supply current | | - | 25 | mA |
| I _{GND} | ground current | | -25 | - | mA |
| T _{stg} | storage temperature | | -65 | +150 | °C |
| P _{tot} | total power dissipation | T _{amb} = -40 °C to +125 °C | [2] - | 200 | mW |

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

[2] Above 55 °C, the value of P_{tot} derates linearly with 2.5 mW/K.

10. Recommended operating conditions

Table 6. Recommended operating conditions

Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | 74HC1G14-Q100 | | | 74HCT1G14-Q100 | | | Unit |
|-----------------|----------------|------------|---------------|-----|-----|----------------|-----|-----|------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| V _{CC} | supply voltage | | 2.0 | 5.0 | 6.0 | 4.5 | 5.0 | 5.5 | V |

Table 6. Recommended operating conditions ...continued
 Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | 74HC1G14-Q100 | | | 74HCT1G14-Q100 | | | Unit |
|-----------|---------------------|------------|---------------|-----|----------|----------------|-----|----------|------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| V_I | input voltage | | 0 | - | V_{CC} | 0 | - | V_{CC} | V |
| V_O | output voltage | | 0 | - | V_{CC} | 0 | - | V_{CC} | V |
| T_{amb} | ambient temperature | | -40 | +25 | +125 | -40 | +25 | +125 | °C |

11. Static characteristics

Table 7. Static characteristics

Voltages are referenced to GND (ground = 0 V). All typical values are measured at $T_{amb} = 25\text{ °C}$.

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|--------|-----------|------------|------------------|-----|-----|-------------------|-----|------|
| | | | Min | Typ | Max | Min | Max | |

For type 74HC1G14-Q100

| | | | | | | | | |
|----------|----------------------------------|--|------|------|------|-----|------|---------------|
| V_{OH} | HIGH-level output voltage | $V_I = V_{T+}$ or V_{T-} | | | | | | |
| | | $I_O = -20\text{ }\mu\text{A}; V_{CC} = 2.0\text{ V}$ | 1.9 | 2.0 | - | 1.9 | - | V |
| | | $I_O = -20\text{ }\mu\text{A}; V_{CC} = 4.5\text{ V}$ | 4.4 | 4.5 | - | 4.4 | - | V |
| | | $I_O = -20\text{ }\mu\text{A}; V_{CC} = 6.0\text{ V}$ | 5.9 | 6.0 | - | 5.9 | - | V |
| | | $I_O = -2.0\text{ mA}; V_{CC} = 4.5\text{ V}$ | 4.13 | 4.32 | - | 3.7 | - | V |
| | | $I_O = -2.6\text{ mA}; V_{CC} = 6.0\text{ V}$ | 5.63 | 5.81 | - | 5.2 | - | V |
| V_{OL} | LOW-level output voltage | $V_I = V_{T+}$ or V_{T-} | | | | | | |
| | | $I_O = 20\text{ }\mu\text{A}; V_{CC} = 2.0\text{ V}$ | - | 0 | 0.1 | - | 0.1 | V |
| | | $I_O = 20\text{ }\mu\text{A}; V_{CC} = 4.5\text{ V}$ | - | 0 | 0.1 | - | 0.1 | V |
| | | $I_O = 20\text{ }\mu\text{A}; V_{CC} = 6.0\text{ V}$ | - | 0 | 0.1 | - | 0.1 | V |
| | | $I_O = 2.0\text{ mA}; V_{CC} = 4.5\text{ V}$ | - | 0.15 | 0.33 | - | 0.4 | V |
| | | $I_O = 2.6\text{ mA}; V_{CC} = 6.0\text{ V}$ | - | 0.16 | 0.33 | - | 0.4 | V |
| I_I | input leakage current | $V_I = V_{CC}$ or GND; $V_{CC} = 6.0\text{ V}$ | - | - | 1.0 | - | 1.0 | μA |
| I_{CC} | supply current | $V_I = V_{CC}$ or GND; $I_O = 0\text{ A}; V_{CC} = 6.0\text{ V}$ | - | - | 10 | - | 20 | μA |
| C_I | input capacitance | | - | 1.5 | - | - | - | pF |
| V_{T+} | positive-going threshold voltage | see Figure 7 and 8 | | | | | | |
| | | $V_{CC} = 2.0\text{ V}$ | 0.7 | 1.09 | 1.5 | 0.7 | 1.5 | V |
| | | $V_{CC} = 4.5\text{ V}$ | 1.7 | 2.36 | 3.15 | 1.7 | 3.15 | V |
| | | $V_{CC} = 6.0\text{ V}$ | 2.1 | 3.12 | 4.2 | 2.1 | 4.2 | V |
| V_{T-} | negative-going threshold voltage | see Figure 7 and 8 | | | | | | |
| | | $V_{CC} = 2.0\text{ V}$ | 0.3 | 0.60 | 0.9 | 0.3 | 0.9 | V |
| | | $V_{CC} = 4.5\text{ V}$ | 0.9 | 1.53 | 2.0 | 0.9 | 2.0 | V |
| | | $V_{CC} = 6.0\text{ V}$ | 1.2 | 2.08 | 2.6 | 1.2 | 2.6 | V |
| V_H | hysteresis voltage | see Figure 7 and 8 | | | | | | |
| | | $V_{CC} = 2.0\text{ V}$ | 0.2 | 0.48 | 1.0 | 0.2 | 1.0 | V |
| | | $V_{CC} = 4.5\text{ V}$ | 0.4 | 0.83 | 1.4 | 0.4 | 1.4 | V |
| | | $V_{CC} = 6.0\text{ V}$ | 0.6 | 1.04 | 1.6 | 0.6 | 1.6 | V |

Table 7. Static characteristics ...continued

Voltages are referenced to GND (ground = 0 V). All typical values are measured at $T_{amb} = 25\text{ }^{\circ}\text{C}$.

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|--------------------------------|----------------------------------|---|------------------|------|------|-------------------|-----|---------------|
| | | | Min | Typ | Max | Min | Max | |
| For type 74HCT1G14-Q100 | | | | | | | | |
| V_{OH} | HIGH-level output voltage | $V_I = V_{T+}$ or V_{T-} | | | | | | |
| | | $I_O = -20\text{ }\mu\text{A}$; $V_{CC} = 4.5\text{ V}$ | 4.4 | 4.5 | - | 4.4 | - | V |
| | | $I_O = -2.0\text{ mA}$; $V_{CC} = 4.5\text{ V}$ | 4.13 | 4.32 | - | 3.7 | - | V |
| V_{OL} | LOW-level output voltage | $V_I = V_{T+}$ or V_{T-} | | | | | | |
| | | $I_O = 20\text{ }\mu\text{A}$; $V_{CC} = 4.5\text{ V}$ | - | 0 | 0.1 | - | 0.1 | V |
| | | $I_O = 2.0\text{ mA}$; $V_{CC} = 4.5\text{ V}$ | - | 0.15 | 0.33 | - | 0.4 | V |
| I_I | input leakage current | $V_I = V_{CC}$ or GND; $V_{CC} = 5.5\text{ V}$ | - | - | 1.0 | - | 1.0 | μA |
| I_{CC} | supply current | $V_I = V_{CC}$ or GND; $I_O = 0\text{ A}$; $V_{CC} = 5.5\text{ V}$ | - | - | 10 | - | 20 | μA |
| ΔI_{CC} | additional supply current | per input; $V_{CC} = 4.5\text{ V}$ to 5.5 V ; $V_I = V_{CC} - 2.1\text{ V}$; $I_O = 0\text{ A}$ | - | - | 500 | - | 850 | μA |
| C_I | input capacitance | | - | 1.5 | - | - | - | pF |
| V_{T+} | positive-going threshold voltage | see Figure 7 and 8 | | | | | | |
| | | $V_{CC} = 4.5\text{ V}$ | 1.2 | 1.55 | 1.9 | 1.2 | 1.9 | V |
| | | $V_{CC} = 5.5\text{ V}$ | 1.4 | 1.80 | 2.1 | 1.4 | 2.1 | V |
| V_{T-} | negative-going threshold voltage | see Figure 7 and 8 | | | | | | |
| | | $V_{CC} = 4.5\text{ V}$ | 0.5 | 0.76 | 1.2 | 0.5 | 1.2 | V |
| | | $V_{CC} = 5.5\text{ V}$ | 0.6 | 0.90 | 1.4 | 0.6 | 1.4 | V |
| V_H | hysteresis voltage | see Figure 7 and 8 | | | | | | |
| | | $V_{CC} = 4.5\text{ V}$ | 0.4 | 0.80 | - | 0.4 | - | V |
| | | $V_{CC} = 5.5\text{ V}$ | 0.4 | 0.90 | - | 0.4 | - | V |

12. Dynamic characteristics

Table 8. Dynamic characteristics

$GND = 0\text{ V}$; $t_r = t_f \leq 6.0\text{ ns}$; All typical values are measured at $T_{amb} = 25\text{ }^{\circ}\text{C}$. For test circuit see [Figure 6](#)

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|-------------------------------|-------------------------------|--|------------------|-----|-----|-------------------|-----|------|
| | | | Min | Typ | Max | Min | Max | |
| For type 74HC1G14-Q100 | | | | | | | | |
| t_{pd} | propagation delay | A to Y; see Figure 5 | | | | | | |
| | | $V_{CC} = 2.0\text{ V}$; $C_L = 50\text{ pF}$ | - | 25 | 155 | - | 190 | ns |
| | | $V_{CC} = 4.5\text{ V}$; $C_L = 50\text{ pF}$ | - | 12 | 31 | - | 38 | ns |
| | | $V_{CC} = 5.0\text{ V}$; $C_L = 15\text{ pF}$ | - | 10 | - | - | - | ns |
| | | $V_{CC} = 6.0\text{ V}$; $C_L = 50\text{ pF}$ | - | 11 | 26 | - | 32 | ns |
| C_{PD} | power dissipation capacitance | $V_I = GND$ to V_{CC} | - | 20 | - | - | - | pF |

Table 8. Dynamic characteristics ...continued

$GND = 0\text{ V}$; $t_r = t_f \leq 6.0\text{ ns}$; All typical values are measured at $T_{amb} = 25\text{ }^\circ\text{C}$. For test circuit see [Figure 6](#)

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|--------------------------------|-------------------------------|--|---------------------|-----|-----|-------------------|-----|------|
| | | | Min | Typ | Max | Min | Max | |
| For type 74HCT1G14-Q100 | | | | | | | | |
| t_{pd} | propagation delay | A to Y; see Figure 5 | [1] | | | | | |
| | | $V_{CC} = 4.5\text{ V}$; $C_L = 50\text{ pF}$ | - | 17 | 43 | - | 51 | ns |
| | | $V_{CC} = 5.0\text{ V}$; $C_L = 15\text{ pF}$ | - | 15 | - | - | - | ns |
| C_{PD} | power dissipation capacitance | $V_I = GND$ to $V_{CC} - 1.5\text{ V}$ | [2] | 22 | - | - | - | pF |

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .

[2] C_{PD} is used to determine the dynamic power dissipation P_D (μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i + \sum (C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

f_i = input frequency in MHz; f_o = output frequency in MHz

C_L = output load capacitance in pF; V_{CC} = supply voltage in Volts

$\sum (C_L \times V_{CC}^2 \times f_o)$ = sum of outputs

13. Waveforms





Table 9. Measurement points

| Type number | Input | | Output |
|----------------|-----------------|---------------------|---------------------|
| | V_I | V_M | V_M |
| 74HC1G14-Q100 | GND to V_{CC} | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |
| 74HCT1G14-Q100 | GND to 3.0 V | 1.5 V | $0.5 \times V_{CC}$ |



Test data is given in [Table 8](#). Definitions for test circuit:

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to output impedance Z_o of the pulse generator.

Fig 6. Load circuitry for switching times

14. Transfer characteristics waveforms




Fig 7. Transfer characteristic




Fig 8. The definitions of V_{T+} , V_{T-} and V_H ; where V_{T+} and V_{T-} are between limits of 20 % and 70 %




Fig 9. Typical 74HC1G14-Q100 transfer characteristics; $V_{CC} = 2.0$ V




Fig 10. Typical 74HC1G14-Q100 transfer characteristics; $V_{CC} = 4.5$ V




Fig 11. Typical 74HC1G14-Q100 transfer characteristics; V_{CC} = 6.0 V




Fig 12. Typical 74HCT1G14-Q100 transfer characteristics; V_{CC} = 4.5 V




Fig 13. Typical 74HCT1G14-Q100 transfer characteristics; V_{CC} = 5.5 V

15. Application information

The slow input rise and fall times cause additional power dissipation. The additional power dissipation can be calculated using the following formula:

$$P_{add} = f_i \times (t_r \times \Delta I_{CC(AV)} + t_f \times \Delta I_{CC(AV)}) \times V_{CC}$$

Where:

P_{add} = additional power dissipation (μW)

f_i = input frequency (MHz)

t_r = rise time (ns); 10 % to 90 %

t_f = fall time (ns); 90 % to 10 %

$\Delta I_{CC(AV)}$ = average additional supply current (μA)

$\Delta I_{CC(AV)}$ differs with positive or negative input transitions, as shown in [Figure 14](#) and [15](#).

74HC1G14-Q100 and 74HCT1G14-Q100 used in relaxation oscillator circuit, see [Figure 16](#).

Remark: All values given are typical unless otherwise specified.




Fig 14. $\Delta I_{CC(AV)}$ for 74HC1G14-Q100 devices; linear change of V_I between $0.1 \times V_{CC}$ to $0.9 \times V_{CC}$






Fig 15. $\Delta I_{CC(AV)}$ for 74HCT1G14-Q100 devices; linear change of V_I between $0.1 \times V_{CC}$ to $0.9 \times V_{CC}$




For 74HC1G14-Q100 and 74HCT1G14-Q100: $f = \frac{1}{T} \approx \frac{1}{K \times RC}$

For K-factor, see [Figure 17](#)

Fig 16. Relaxation oscillator



K-factor for 74HC1G14-Q100



K-factor for 74HCT1G14-Q100

Fig 17. Typical K-factor for relaxation oscillator

16. Package outline

TSSOP5: plastic thin shrink small outline package; 5 leads; body width 1.25 mm

SOT353-1




Fig 18. Package outline SOT353-1 (TSSOP5)

Plastic surface-mounted package; 5 leads

SOT753




Fig 19. Package outline SOT753 (SC-74A)

17. Abbreviations

Table 10. Abbreviations

| Acronym | Description |
|---------|-----------------------------|
| DUT | Device Under Test |
| TTL | Transistor-Transistor Logic |

18. Revision history

Table 11. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|-----------------------|---|--------------------|---------------|-----------------------|
| 74HC_HCT1G14_Q100 v.2 | 20121227 | Product data sheet | - | 74HC_HCT1G14_Q100 v.1 |
| Modifications: | • Table 3 : Pin number Y output changed from 5 to 4 (errata). | | | |
| 74HC_HCT1G14_Q100 v.1 | 20120820 | Product data sheet | - | - |

19. Legal information

19.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

19.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

19.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use in automotive applications — This NXP Semiconductors product has been qualified for use in automotive applications. Unless otherwise agreed in writing, the product is not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

19.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

20. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

21. Contents

| | | |
|-----------|---|-----------|
| 1 | General description | 1 |
| 2 | Features and benefits | 1 |
| 3 | Applications | 1 |
| 4 | Ordering information | 2 |
| 5 | Marking | 2 |
| 6 | Functional diagram | 2 |
| 7 | Pinning information | 2 |
| 7.1 | Pinning | 2 |
| 7.2 | Pin description | 3 |
| 8 | Functional description | 3 |
| 9 | Limiting values | 3 |
| 10 | Recommended operating conditions | 3 |
| 11 | Static characteristics | 4 |
| 12 | Dynamic characteristics | 5 |
| 13 | Waveforms | 6 |
| 14 | Transfer characteristics waveforms | 7 |
| 15 | Application information | 8 |
| 16 | Package outline | 11 |
| 17 | Abbreviations | 13 |
| 18 | Revision history | 13 |
| 19 | Legal information | 14 |
| 19.1 | Data sheet status | 14 |
| 19.2 | Definitions | 14 |
| 19.3 | Disclaimers | 14 |
| 19.4 | Trademarks | 15 |
| 20 | Contact information | 15 |
| 21 | Contents | 16 |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2012.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 27 December 2012

Document identifier: 74HC_HCT1G14_Q100