


FEATURES

- . Silicon planar power zener diodes
- For use in stabilizing and clipping circuits with high power rating.
- . Standards Zener voltage toerance is $\pm 10\%$
- Add suffix "A" for $\pm 5\%$ tolerance Other tolerance available upon request

DO-41(GLASS)



Dimensions in inches and (millimeters)

MECHANICAL DATA

- . **Case:** DO-41 glass case
- . **weight:** Approx. 0.35 gram

ABSOLUTE MAXIMUM RATINGS(LIMITING VALUES)(TA=25°C)

	Symbols	Value	Units
Zener current see table "Characteristics"			
Power dissipation at TA=25°C	P _{tot}	1 ¹⁾	mW
Junction temperature	T _J	175	°C
Storage temperature range	T _{STG}	-65 to +175	°C

1)Valid provided that a distance of 8mm from case are kept at ambient temperature

ELECTRCAL CHARACTERISTICS(TA=25°C)

	Symbols	Min	Typ	Max	Units
Thermal resistance junction to ambient	R _{thA}			170 ¹⁾	°C/W
Forward voltage at IF=200mA	V _F			1.2	V

1) Valid provided that a distance at 8mm from case are kept at ambient temperature

1N4728..1N4764 SILICON PLANAR ZENER DIODES

Type	Nominal Zener Voltage ³⁾	Test Current	Maximum Zener Impedance ¹⁾			Maximum reverse leakage current		Surge current	Maximum regulator Current ²⁾	
	at I_{ZT} V_Z V	I_{ZT} mA	at I_{ZT} Z_{ZT} Ω	Z_{ZK} Ω	at I_{ZK} mA	I_R μ A	at V_R V	at $T_A=0.25$ I_R mA	I_{ZM} mA	
1N4728	3.3	76	10	400	1.0	100	1.0	1380	276	
1N4729	3.6	69	10				1.0	1260	252	
1N4730	3.9	64	9			50	1.0	1190	234	
1N4731	4.3	58	9	1.0			1070	217		
1N4732	4.7	53	8	500		1.0	970	193		
1N4733	5.1	49	7	550		1.0	890	178		
1N4734	5.6	45	5	600		10	2.0	810	162	
1N4735	6.2	41	2	700			3.0	730	146	
1N4736	6.8	37	3.5				4.0	660	133	
1N4737	7.5	34	4.0				5.0	5.0	605	121
1N4738	8.2	31	4.5		6.0			550	110	
1N4739	9.1	28	5.0		0.25		7.0	500	100	
1N4740	10	25	7				7.6	454	91	
1N4741	11	23	8				5	8.4	414	83
1N4742	12	21	9					9.1	380	76
1N4743	13	19	10					9.9	344	69
1N4744	15	17	14			11.4		304	61	
1N4745	16	15.5	16	12.2		285		57		
1N4746	18	14	20	750		13.7		250	50	
1N4747	20	12.5	22			15.2		225	45	
1N4748	22	11.5	23			16.7		205	41	
1N4749	24	10.5	25		18.2	190		38		
1N4750	27	9.5	35		20.6	170		34		
1N4751	30	8.5	40		1000	22.8	150	30		
1N4752	33	7.5	45			25.1	135	27		
1N4753	36	7.0	50			27.4	125	25		
1N4754	39	6.5	60			29.7	115	23		
1N4755	43	6.0	70			1500	32.7	110	22	
1N4756	47	5.5	80	35.8			95	19		
1N4757	51	5.0	95	38.8			90	18		
1N4758	56	4.5	110	42.6			80	16		
1N4759	62	4.0	125	2000			47.1	70	14	
1N4760	68	3.7	150				51.7	65	13	
1N4761	75	3.3	175		56.0		60	12		
1N4762	82	3.0	200		3000		62.2	55	11	
1N4763	91	2.8	250				69.2	50	10	
1N4764	100	2.5	350				76.0	45	9	

Notes:1) The Zener impedance is derived from the 1KHz AC voltage which results when an AC current having an RMS value equal to 10% of the Zener current(I_{ZT} or I_{ZK}) is superimposed on I_{ZT} or I_{ZK} . Zener impedance is measured at two points to insure a sharp knee on the breakdown curve and to eliminate unstable units.

2)Valid provided that electrodes at a distance of 10mm from case are kept at ambient temperature

3)Measured under thermal equilibrium and DC test conditions.

RATINGS AND CHARACTERISTIC CURVES 1N4728 THRU 1N4764

Admissible power dissipation versus ambient temperature
(Valid provided that leads at a distance of 10mm from case
are kept at ambient temperature)

