



BZX84C - SERIES

SURFACE MOUNT ZENER DIODES/SOT - 23

Ta = 25°C		Marking Code	Zener Voltage @ Izt		Max. Dyn. Imped. @ Izt	Test Current	Max. Dyn. Imped. @ Izk	Test Current	Temp Coeff. @ Izt	Rev. Current @ Vr	Test Voltage
Part No.	Cross-Reference		Vz (V)	Zzt (Ω)	Izt (mA)	Zzk (Ω)	Izk (mA)	avz (%/K)	Ir (μA)	Vr (V)	
			BZX84C2V7	MMBZ5223B	Z12	2.5 - 2.9	100	600		-0.065	20.00
BZX84C3	MMBZ5225B	Z13	2.8 - 3.2	95	600		-0.060	10.00	1.0		
BZX84C3V3	MMBZ5226B	Z14	3.1 - 3.5	95	600		-0.055	5.00	1.0		
BZX84C3V6	MMBZ5227B	Z15	3.4 - 3.8	90	600		-0.055	5.00	1.0		
BZX84C3V9	MMBZ5228B	Z16	3.7 - 4.1	90	600		-0.050	3.00	1.0		
BZX84C4V3	MMBZ5229B	Z17	4.0 - 4.6	90	600		-0.035	3.00	1.0		
BZX84C4V7	MMBZ5230B	Z1	4.4 - 5.0	80	500		-0.015	3.00	2.0		
BZX84C5V1	MMBZ5231B	Z2	4.8 - 5.4	60	480		+0.005	2.00	2.0		
BZX84C5V6	MMBZ5232B	Z3	5.2 - 6.0	40	400	5.0	+0.020	1.00	2.0		
BZX84C6V2	MMBZ5234B	Z4	5.8 - 6.6	10	150		+0.030	3.00	4.0		
BZX84C6V8	MMBZ5235B	Z5	6.4 - 7.2	15	80		+0.045	2.00	4.0		
BZX84C7V5	MMBZ5236B	Z6	7.0 - 7.9	15	80		+0.050	1.00	5.0		
BZX84C8V2	MMBZ5237B	Z7	7.7 - 8.7	15	80		+0.055	0.70	5.0		
BZX84C9V1	MMBZ5239B	Z8	8.5 - 9.6	15	100		+0.065	0.50	6.0		
BZX84C10	MMBZ5240B	Z9	9.4 - 10.6	20	150		+0.065	0.20	7.0		
BZX84C11	MMBZ5241B	Y1	10.4 - 11.6	20	150		+0.070	0.10	8.0		
BZX84C12	MMBZ5242B	Y2	11.4 - 12.7	25	150		+0.075	0.10	8.0		
BZX84C13	MMBZ5243B	Y3	12.4 - 14.1	30	170		+0.080	0.10	8.0		
BZX84C15	MMBZ5245B	Y4	13.8 - 15.6	30	200		+0.090	0.05	0.7		
BZX84C16	MMBZ5246B	Y5	15.3 - 17.1	40	200	+0.090	0.05	0.7			
BZX84C18	MMBZ5248B	Y6	16.8 - 19.1	45	225	+0.090	0.05	0.7			
BZX84C20	MMBZ5250B	Y7	18.8 - 21.2	55	225	+0.090	0.05	0.7			
BZX84C22	MMBZ5251B	Y8	20.8 - 23.3	55	250	+0.090	0.05	0.7			
BZX84C24	MMBZ5252B	Y9	22.8 - 25.6	70	250	+0.090	0.05	0.7			
BZX84C27	MMBZ5254B	Y10	25.1 - 28.9	80	300	2.0	+0.090	0.05	0.7		
BZX84C30	MMBZ5256B	Y11	28 - 32	80	300		+0.090				
BZX84C33	MMBZ5257B	Y12	31 - 35	80	325		+0.090				
BZX84C36	MMBZ5258B	Y13	34 - 38	90	350		+0.090				
BZX84C39	MMBZ5259B	Y14	37 - 41	130	350		+0.110				
BZX84C43	MMBZ5260B	Y15	40 - 46	150	375		+0.110				
BZX84C47	MMBZ5261B	Y16	44 - 50	170	375		+0.110				
BZX84C51	MMBZ5262B	Y17	48 - 54	180	400		+0.110				

Notes: 1. Operating and storage Temperature Range:

- 55°C to + 150°C

2. Package outline/SOT - 23 pin configuration - topview as figure.

