

FAIRCHILD

A Schlumberger Company

2N4123/FTSO4123
2N4124/FTSO4124

T-35-11

NPN Small Signal General Purpose Amplifiers & Switches

- V_{CEO} ... 25 V (Min) (2N/FTSO4124)
- h_{FE} ... 120-360 @ 2.0 mA (2N/FTSO4124)
- NF ... 5.0 dB (Max) Wide Band (2N/FTSO4124)
- Complements ... 2N4125, 2N4126

PACKAGE

2N4123	TO-92
2N4124	TO-92
FTSO4123	TO-236AA/AB
FTSO4124	TO-236AA/AB

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

Storage Temperature	-55° C to 150° C
Operating Junction Temperature	150° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at	2N	FTSO
25° C Ambient Temperature	0.625 W	0.350 W*
70° C Ambient Temperature	0.400 W	
25° C Case Temperature	1.0 W	

Voltages & Currents

	4123	4124
V_{CEO} Collector to Emitter Voltage (Note 4)	30 V	25 V
V_{CBO} Collector to Base Voltage	40 V	30 V
V_{EBO} Emitter to Base Voltage	5.0 V	5.0 V
I_C Collector Current	200 mA	200 mA

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	4123		4124		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CEO}	Collector to Emitter Breakdown Voltage (Note 5)	30		25		V	$I_C = 1.0$ mA, $I_B = 0$
BV_{CBO}	Collector to Base Breakdown Voltage	40		30		V	$I_C = 10$ μ A, $I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	5.0		5.0		V	$I_E = 10$ μ A, $I_C = 0$
I_{EBO}	Emitter Cutoff Current		50		50	nA	$V_{EB} = 3.0$ V, $I_C = 0$
I_{CBO}	Collector Cutoff Current		50		50	nA	$V_{CB} = 20$ V, $I_E = 0$
h_{FE}	DC Pulse Current Gain (Note 5)	50	150	120	360		$I_C = 2.0$ mA, $V_{CE} = 1.0$ V $I_C = 50$ mA, $V_{CE} = 1.0$ V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Note 5)		0.3		0.3	V	$I_C = 50$ mA, $I_B = 5.0$ mA

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
 2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
 3. These ratings give a maximum junction temperature of 150° C and (TO-92) junction-to-case thermal resistance of 125° C/W (derating factor of 8.0 mW/° C); junction-to-ambient thermal resistance of 200° C/W (derating factor of 5.0 mW/° C); (TO-236) junction-to-ambient thermal resistance of 357° C/W (derating factor of 2.8 mW/° C).
 4. Rating refers to a high current point where collector to emitter voltage is lowest.
 5. Pulse conditions: length = 300 μ s; duty cycle = 2%.
 6. For product family characteristic curves, refer to Curve Set T144.
- * Package mounted on 99.5% alumina 8 mm x 8 mm x 0.6 mm.



2N4125/FTSO4125
2N4126/FTSO4126

PNP Small Signal General Purpose Amplifiers & Switches

T-35-11

- V_{CE0} ... -25 V (Min) (2N/FTSO4126)
- h_{FE} ... 120-360 @ 2.0 mA (2N/FTSO4126)
- NF ... 4.0 dB (Max) Wide Band (2N/FTSO4126)
- Complements ... 2N4123, 2N4124

PACKAGE	
2N4125	TO-92
2N4126	TO-92
FTSO4125	TO-236AA/AB
FTSO4126	TO-236AA/AB

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures	
Storage Temperature	-55° C to 150° C
Operating Junction Temperature	150° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at	2N	FTSO
25° C Ambient Temperature	0.625 W	0.350 W*
70° C Ambient Temperature	0.400 W	
25° C Case Temperature	1.0 W	

Voltages & Currents	4125	4126
V_{CE0} Collector to Emitter Voltage (Note 4)	-30 V	-25 V
V_{CBO} Collector to Base Voltage	-30 V	-25 V
V_{EBO} Emitter to Base Voltage	-4.0 V	-4.0 V
I_C Collector Current	200 mA	200 mA

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	4125		4126		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CE0}	Collector to Emitter Breakdown Voltage (Note 5)	-30		-25		V	$I_C = 1.0 \text{ mA}, I_B = 0$
BV_{CBO}	Collector to Base Breakdown Voltage	-30		-25		V	$I_C = 10 \mu\text{A}, I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	-4.0		-4.0		V	$I_E = 10 \mu\text{A}, I_C = 0$
I_{EBO}	Emitter Cutoff Current		50		50	nA	$V_{EB} = -3.0 \text{ V}, I_C = 0$
I_{CBO}	Collector Cutoff Current		50		50	nA	$V_{CB} = -20 \text{ V}, I_E = 0$
h_{FE}	DC Pulse Current Gain (Note 5)		150	120	360		$I_C = 2.0 \text{ mA}, V_{CE} = -1.0 \text{ V}$
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Note 5)		-0.4		-0.4	V	$I_C = 50 \text{ mA}, I_B = 5.0 \text{ mA}$
$V_{BE(sat)}$	Base to Emitter Saturation Voltage (Note 5)		-0.95		-0.95	V	$I_C = 50 \text{ mA}, I_B = 5.0 \text{ mA}$

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
 2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
 3. These ratings give a maximum junction temperature of 150° C and (TO-92) junction-to-case thermal resistance of 125° C/W (derating factor of 8.0 mW/° C); junction-to-ambient thermal resistance of 200° C/W (derating factor of 5.0 mW/° C); (TO-236) junction-to-ambient thermal resistance of 357° C/W (derating factor of 2.8 mW/° C).
 4. Rating refers to a high current point where collector to emitter voltage is lowest.
 5. Pulse conditions: length = 300 μ s; duty cycle = 2%.
 6. For product family characteristic curves, refer to Curve Set T215.
- * Package mounted on 99.5% alumina 8 mm x 8 mm x 0.6 mm.

2N4125/FTSO4125
2N4126/FTSO4126

T-35-11

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	4125		4126		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
C_{cb}	Collector to Base Capacitance		4.5		4.5	pF	$V_{CB} = -5.0 \text{ V}$, $I_E = 0$, $f = 100 \text{ kHz}$
C_{ib}	Input Capacitance		10		10	pF	$V_{EB} = -0.5 \text{ V}$, $I_C = 0$, $f = 100 \text{ kHz}$
$ h_{fe} $	Magnitude of Small Signal Current Gain	2.0		2.0			$I_C = 10 \text{ mA}$, $V_{CE} = -20 \text{ V}$, $f = 100 \text{ MHz}$
h_{fe}	Small Signal Current Gain	50	200	120	480		$I_C = 2.0 \text{ mA}$, $V_{CE} = -1.0 \text{ V}$, $f = 1.0 \text{ kHz}$
NF	Noise Figure		5.0		4.0	dB	$I_C = 100 \mu\text{A}$, $V_{CE} = -5.0 \text{ V}$, $f = 10 \text{ Hz to } 15.7 \text{ kHz}$, $R_E = 1.0 \text{ k}\Omega$

3469674 FAIRCHILD SEMICONDUCTOR

84D 27575 D

FAIRCHILD

A Schlumberger Company

2N4208/FTSO4208 T-37-07
2N4209/FTSO4209

PNP Small Signal Ultra High Speed Saturated Switches

- V_{CE0} ... 15 V (Min) (2N/FTSO4209)
- V_{CE} ... 0.18 V (Max) @ $I_C = 10$ mA (2N/FTSO4209)
- τ_B ... 20 ns (Max)
- t_{on} ... 15 ns (Max), t_{off} ... 20 ns (Max)
- C_{ob} ... 3.0 pF (Max)
- C_{ib} ... 3.5 pF (Max)
- f_T ... 850 MHz (Min) (2N/FTSO4209)
- Complement ... 2N2369A

PACKAGE	
2N4208	TO-18
2N4209	TO-18
FTSO4208	TO-236AA/AB
FTSO4209	TO-236AA/AB

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures	2N	FTSO
Storage Temperature	-65° C to 200° C	-55° C to 150° C
Operating Junction Temperature	200° C	150° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at	2N	FTSO
25° C Ambient Temperature	0.3 W	0.350 W*
25° C Case Temperature	0.7 W	

Voltages & Currents

	4208	4209
V_{CE0} Collector to Emitter Voltage (Note 4)	-12 V	-15 V
V_{CBO} Collector to Base Voltage	-12 V	-15 V
V_{EBO} Emitter to Base Voltage	-4.5 V	-4.5 V
I_C Collector Current	50 mA	50 mA

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	4208		4209		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CES}	Collector to Emitter Breakdown Voltage	-12		-15		V	$I_C = 100 \mu A, V_{BE} = 0$
BV_{CBO}	Collector to Base Breakdown Voltage	-12		-15		V	$I_C = 100 \mu A, I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	-4.5		-4.5		V	$I_E = 100 \mu A, I_C = 0$

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
 2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
 3. These ratings give a maximum junction temperature of 200° C and (TO-92) junction-to-case thermal resistance of 250° C/W (derating factor of 4.0 mW/° C); junction-to-ambient thermal resistance of 583° C/W (derating factor of 1.72 mW/° C); (TO-236) junction-to-ambient thermal resistance of 357° C/W (derating factor of 2.8 mW/° C).
 4. Rating refers to a high current point where collector to emitter voltage is lowest.
 5. Pulse conditions: length = 300 μs ; duty cycle = 1%.
 6. For product family characteristic curves, refer to Curve Set T292.
- * Package mounted on 99.5% alumina 8 mm x 8 mm x 0.6 mm.

2N4208/FTSO4208

2N4209/FTSO4209

T-37-07

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	4208		4209		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
I_{CES}	Collector Reverse Current (Note 5)		10		10	nA	$V_{CE} = -6.0\text{ V}, V_{BE} = 0$ $V_{CE} = -8.0\text{ V}, V_{BE} = 0$ $V_{CE} = -6.0\text{ V}, V_{BE} = 0,$ $T_A = 125^\circ\text{ C}$ $V_{CE} = -8.0\text{ V}, V_{BE} = 0,$ $T_A = 125^\circ\text{ C}$
			5.0		5.0	μA	
						μA	
h_{FE}	DC Current Gain	15		35			$I_C = 1.0\text{ mA}, V_{CE} = -0.5\text{ V}$
h_{FE}	DC Pulse Current Gain (Note 5)	30	120	50	120		$I_C = 10\text{ mA}, V_{CE} = -0.3\text{ V}$ $I_C = 50\text{ mA}, V_{CE} = -1.0\text{ V}$ $I_C = 10\text{ mA}, V_{CE} = -0.3\text{ V},$ $T_A = -55^\circ\text{ C}$
		30		40			
		12		20			
$V_{CE(sus)}$	Collector to Emitter Sustaining Voltage (Note 5)	-12		-15		V	$I_C = 3.0\text{ mA}, I_B = 0$
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage		-0.13		-0.15	V	$I_C = 1.0\text{ mA}, I_B = 0.1\text{ mA}$
$V_{CE(sat)}$	Pulsed Collector to Emitter Saturation Voltage (Note 5)		-0.15		-0.18	V	$I_C = 10\text{ mA}, I_B = 1.0\text{ mA}$ $I_C = 50\text{ mA}, I_B = 5.0\text{ mA}$
			-0.5		-0.6	V	
$V_{BE(sat)}$	Base to Emitter Saturation Voltage		-0.8		-0.8	V	$I_C = 1.0\text{ mA}, I_B = 0.1\text{ mA}$
$V_{BE(sat)}$	Pulsed Base to Emitter Saturation Voltage (Note 5)	-0.8	-0.95	-0.8	-0.95	V	$I_C = 10\text{ mA}, I_B = 1.0\text{ mA}$ $I_C = 50\text{ mA}, I_B = 5.0\text{ mA}$
			-1.5		-1.5	V	
C_{ob}	Output Capacitance		3.0		3.0	pF	$V_{CB} = -5.0\text{ V}, I_E = 0$
C_{ib}	Input Capacitance		3.5		3.5	pF	$V_{BE} = -0.5\text{ V}, I_C = 0$
f_{tfe}	High Frequency Current Gain		7.0		8.5		$I_C = 10\text{ mA}, V_{CE} = -10\text{ V},$ $f = 100\text{ MHz}$
τ_s	Charge Storage Time Constant (test circuit no. 234)		20		20	ns	$I_C = 10\text{ mA}, I_{B1} = I_{B2} \approx 10\text{ mA},$ $V_{CC} = -3.0\text{ V}$
t_{on}	Turn On Time (test circuit no. 348)		15		15	ns	$I_C = 10\text{ mA}, I_{B1} \approx 1.0\text{ mA},$ $V_{CC} = -1.5\text{ V}$
t_{off}	Turn Off Time (test circuit no. 348)		20		20	ns	$I_C = 10\text{ mA}, I_{B1} = I_{B2} \approx 1.0\text{ mA},$ $V_{CC} = -1.5\text{ V}$



2N4234/2N4235 T-33-05
2N4236
 6 Watt PNP Power

- $V_{CE(sat)}$... 0.6 V @ $I_C = 1.0$ A
- Complements ... 2N4237 through 2N4239

PACKAGE	
2N4234	TO-39
2N4235	TO-39
2N4236	TO-39

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures	
Storage Temperature	-65° C to 200° C
Operating Junction Temperature	200° C

Power Dissipation	
Total Dissipation at 25° C Case Temperature	6.0 W

Voltages & Currents	4234	4235	4236
V_{CEO} Collector to Emitter Voltage	-40 V	-60 V	-80 V
V_{CBO} Collector to Base Voltage	-40 V	-60 V	-80 V
V_{EBO} Emitter to Base Voltage	-7.0 V	-7.0 V	-7.0 V
I_C Collector Current (Continuous)	1.0 A	1.0 A	1.0 A
I_B Base Current (Continuous)	0.2 A	0.2 A	0.2 A

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 3)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
I_{EBO}	Emitter Cutoff Current		500	μA	$V_{EB} = -7.0$ V, $I_C = 0$
I_{CBO}	Collector Cutoff Current (2N4234) (2N4235) (2N4236)		100	μA	$V_{CB} = -40$ V, $I_E = 0$
			100	μA	$V_{CB} = -60$ V, $I_E = 0$
			100	μA	$V_{CB} = -80$ V, $I_E = 0$
I_{CEO}	Collector Cutoff Current (2N4235) (2N4236)		1.0	mA	$V_{CE} = -30$ V, $I_B = 0$
			1.0	mA	$V_{CE} = -40$ V, $I_B = 0$
			1.0	mA	$V_{CE} = -60$ V, $I_B = 0$
I_{CEX}	Collector Cutoff Current (2N4234) (2N4234) (2N4235) (2N4235) (2N4236) (2N4237)		100	μA	$V_{CE} = -40$ V, $V_{EB} = -1.5$ V
			1.0	mA	$V_{CE} = -30$ V, $V_{EB} = -1.5$ V, $T_C = 150^\circ C$
			100	μA	$V_{CE} = -60$ V, $V_{EB} = -1.5$ V
			1.0	mA	$V_{CE} = -40$ V, $V_{EB} = -1.5$ V, $T_C = 150^\circ C$
			100	μA	$V_{CE} = -80$ V, $V_{EB} = -1.5$ V
			1.0	mA	$V_{CE} = -60$ V, $V_{EB} = -1.5$ V, $T_C = 150^\circ C$

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
3. These ratings give a maximum junction temperature of 200° C and junction-to-case thermal resistance of 33.3° C/W (derating factor of 34 mW/° C).
4. Rating refers to a high current point where collector to emitter voltage is lowest.
5. Pulse conditions: length = 300 μs ; duty cycle = 2%.
6. For product family characteristic curves, refer to Curve Set T414.

3469674 FAIRCHILD SEMICONDUCTOR

84D 27578 D

2N4234/2N4235
2N4236

T-33-05

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted) (Note 3)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
h_{FE}	DC Pulse Current Gain (Note 5)	40 30 20 10	150		$I_C = 100 \text{ mA}, V_{CE} = -1.0 \text{ V}$ $I_C = 250 \text{ mA}, V_{CE} = -1.0 \text{ V}$ $I_C = 500 \text{ mA}, V_{CE} = -1.0 \text{ V}$ $I_C = 1.0 \text{ A}, V_{CE} = -1.0 \text{ V}$
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Note 5)		-0.6	V	$I_C = 1.0 \text{ A}, I_B = 125 \text{ mA}$
$V_{BE(ON)}$	Base to Emitter "On" Voltage		-1.0	V	$I_C = 250 \text{ mA}, V_{CE} = -1.0 \text{ V}$
$V_{BE(sat)}$	Base to Emitter Saturation Voltage (Note 5)		-1.5	V	$I_C = 1.0 \text{ A}, I_B = 100 \text{ mA}$
C_{ob}	Output Capacitance		100	pF	$V_{CB} = -10 \text{ V}, I_E = 0, f = 100 \text{ kHz}$
$ h_{fe} $	Magnitude of Common Emitter Small Signal Current Gain	3.0			$I_C = 100 \text{ mA}, V_{CE} = -10 \text{ V}, f = 1.0 \text{ MHz}$
h_{fe}	Small Signal Current Gain	25			$I_C = 50 \text{ mA}, V_{CE} = -10 \text{ V}, f = 1.0 \text{ kHz}$



2N4237/2N4238
2N4239
 5 Watt NPN Power

T-33-05

- $V_{CE(sat)}$... 0.6 V @ $I_C = 1.0$ A
- Complements ... 2N4234 through 2N4236

PACKAGE	
2N4237	TO-39
2N4238	TO-39
2N4239	TO-39

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures	
Storage Temperature	-55° C to 200° C
Operating Junction Temperature	200° C

Power Dissipation	
Total Dissipation at	
25° C Ambient Temperature	0.8 W
25° C Case Temperature	5.0 W

Voltages & Currents		4237	4238	4239
V_{CE0} Collector to Emitter Voltage (Note 4)		40 V	60 V	80 V
V_{CBO} Collector to Base Voltage		50 V	80 V	100 V
V_{EBO} Emitter to Base Voltage		6.0 V	6.0 V	6.0 V
I_C Collector Current		1.0 A	1.0 A	1.0 A
I_B Base Current (Note 2)		0.5 A	0.5 A	0.5 A

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
I_{EBO}	Emitter Cutoff Current		0.5	mA	$V_{EB} = 6.0$ V, $I_C = 0$
I_{CBO}	Collector Cutoff Current (4237) (4238) (4239)		0.1	mA	$V_{CB} = 50$ V, $I_E = 0$
			0.1	mA	$V_{CB} = 80$ V, $I_E = 0$
			0.1	mA	$V_{CB} = 100$ V, $I_E = 0$
I_{CEO}	Collector Cutoff Current (4237) (4238) (4239)		1.0	mA	$V_{CE} = 30$ V, $I_B = 0$
			1.0	mA	$V_{CE} = 40$ V, $I_B = 0$
			1.0	mA	$V_{CE} = 60$ V, $I_B = 0$
I_{CEX}	Collector Cutoff Current (4237) (4238) (4238) (4239) (4239) (4239)		0.1	mA	$V_{CE} = 50$ V, $V_{EB} = 1.5$ V
			1.0	mA	$V_{CE} = 30$ V, $V_{EB} = 1.5$ V, $T_C = 150^\circ$ C
			0.1	mA	$V_{CE} = 80$ V, $V_{EB} = 1.5$ V
			0.1	mA	$V_{CE} = 50$ V, $V_{EB} = 1.5$ V, $T_C = 150^\circ$ C
			0.1	mA	$V_{CE} = 100$ V, $V_{EB} = 1.5$ V
			0.1	mA	$V_{CE} = 70$ V, $V_{EB} = 1.5$ V, $T_C = 150^\circ$ C
h_{FE}	DC Pulse Current Gain (Note 5) (4237) (4238) (4239)	30	150		$I_C = 250$ mA, $V_{CE} = 1.0$ V
		30			$I_C = 500$ mA, $V_{CE} = 4.0$ V
		15			$I_C = 1.0$ A, $V_{CE} = 1.0$ V

- NOTES:**
1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired
 2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
 3. These ratings give a maximum junction temperature of 200° C and junction-to-case thermal resistance of 35° C/W (derating factor of 28.5 mW/° C). junction-to-ambient thermal resistance of 218 8° C/W (derating factor of 4.5 mW/° C).
 4. Rating refers to a high current point where collector to emitter voltage is lowest.
 5. Pulse conditions: length = 300 μ s; duty cycle = 2%.
 6. For product family characteristic curves, refer to Curve Set T315.

2N4237/2N4238
2N4239

T.33-05

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Pulsed) (Note 4)		0.6	V	$I_C = 1.0 \text{ A}, I_B = 100 \text{ mA}$
			0.3	V	$I_C = 500 \text{ mA}, I_B = 50 \text{ mA}$
$V_{BE(on)}$	Base to Emitter "On" Voltage (Pulsed) (Note 4)		1.0	V	$I_C = 250 \text{ mA}, V_{CE} = 1.0 \text{ V}$
$V_{BE(sat)}$	Base to Emitter Saturation Voltage (Pulsed) (Note 4)		1.5	V	$I_C = 1.0 \text{ A}, I_B = 100 \text{ mA}$
C_{ob}	Output Capacitance		100	pF	$V_{CB} = 10 \text{ V}, I_C = 0, f = 0.1 \text{ MHz}$
$ h_{fe} $	Magnitude of Common Emitter Small Signal Current Gain	1.0			$I_C = 100 \text{ mA}, V_{CE} = 10 \text{ V}, f = 1.0 \text{ kHz}$
h_{fe}	Small Signal Current Gain	30			$I_C = 100 \text{ mA}, V_{CE} = 10 \text{ V}, f = 1.0 \text{ kHz}$