



MJ15003


NPN PLANAR SILICON TRANSISTOR

**AUDIO POWER AMPLIFIER
DC TO DC CONVERTER**

- High Current Capability
- High Power Dissipation
- Complementary to MJ15004

ABSOLUTE MAXIMUM RATING (Ta=25°C)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V _{CB0}	140	V
Collector-Emitter Voltage	V _{CEO}	140	V
Emitter-Base voltage	V _{EB0}	5	V
Collector Current (DC)	I _C	20	A
Collector Dissipation	P _C	200	W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-50~150	°C



ELECTRICAL CHARACTERISTICS (Ta=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Collector Base Breakdown Voltage	BV _{CB0}	I _C =10 mA I _E =0	140			V
Collector Emitter Breakdown Voltage	BV _{CEO}	I _C =5 mA R _{BE} =∞	140			V
Emitter Base Breakdown Voltage	BV _{EB0}	I _E =5 mA I _C =0	5			V
Collector Cutoff Current	I _{CB0}	V _{CB} =70V I _E =0			0.1	mA
Emitter Cutoff Current	I _{EB0}	V _{EB} =4V I _C =0			0.1	mA
*DC Current Gain	h _{FE1}	V _{CE} =5V I _C =1A	30		150	
DC Current Gain	h _{FE2}	V _{CE} =5V I _C =5A	25			
Collector- Emitter Saturation Voltage	V _{CE(sat)}	I _C =5A I _B =-0.5A			1.0	V