


SIEMENS AKTIENGESSELLSCHAF

Main ratings

Drain-source voltage $V_{DS} = 800 \text{ V}$
Continuous drain current $I_D = 6,5 \text{ A}$
Drain-source on-resistance $R_{DS(on)} = 1,5 \Omega$


N-Channel



Description FREDET with fast-recovery reverse diode, N-channel, enhancement mode

Case Metal case 3A2 in accordance with DIN 41872, or TO 204 AA (TO 3) in accordance with JEDEC. Approx. weight 12 g

Type	Ordering code
BUZ 220	C67078-A1103-A2



Dimensions in mm

Maximum ratings

Description	Symbols	Ratings	Units	Conditions
Drain-source voltage	V_{DS}	800	V	
Drain-gate voltage	V_{DGR}	800	V	$R_{GS} = 20 \text{ k}\Omega$
Continuous drain current	I_D	6,5	A	$T_C = 30^\circ\text{C}$
Pulsed drain current	I_{Dpuls}	26	A	$T_C = 25^\circ\text{C}$
Gate-source voltage	V_{GS}	± 20	V	
Max. power dissipation	P_D	125	W	$T_C = 25^\circ\text{C}$
Operating and storage temperature range	T_j T_{stg}	$-55 \dots +150$	$^\circ\text{C}$	
DIN humidity category		C	—	DIN 40040
IEC climatic category		55/150/56		DIN IEC 68-1





Thermal resistance

Chip – case	$R_{th JC}$	$\leq 1,0$	K/W
Chip – ambient	$R_{th JA}$	≤ 35	K/W

Electrical characteristics(at $T_j = 25^\circ\text{C}$ unless otherwise specified)

Description	Symbol	Characteristics			Unit	Conditions
		min.	typ.	max.		
Static ratings						
Drain-source breakdown voltage	$V_{(BR) DSS}$	800	—	—	V	$V_{GS} = 0V$ $I_D = 0,25mA$
Gate threshold voltage	$V_{GS (th)}$	2,1	3,0	4,0		$V_{DS} = V_{GS}$ $I_D = 1mA$
Zero gate voltage drain current	I_{DSS}	—	20 100	250 1000	μA	$T_J = 25^{\circ}C$ $T_J = 125^{\circ}C$ $V_{DS} = 800V$ $V_{GS} = 0V$
Gate-source leakage current	I_{GSS}	—	10	100	nA	$V_{GS} = 20V$ $V_{DS} = 0V$
Drain-source on-resistance	$R_{DS (on)}$	—	1,4	1,5	Ω	$V_{GS} = 10V$ $I_D = 4,2A$
Dynamic ratings						
Forward transconductance	g_{fs}	1,8	3,4	—	S	$V_{DS} = 25V$ $I_D = 4,2A$
Input capacitance	C_{iss}	—	3,9	5,0	nF	$V_{GS} = 0V$
Output capacitance	C_{oss}	—	200	350	pF	$V_{DS} = 25V$ $f = 1MHz$
Reverse transfer capacitance	C_{rss}	—	80	140		
Turn-on time t_{on} ($t_{on} = t_{d (on)} + t_r$)	$t_{d (on)}$	—	60	90	ns	$V_{CC} = 30V$ $I_D = 2,6A$
	t_r	—	90	140		$V_{GS} = 10V$
Turn-off time t_{off} ($t_{off} = t_{d (off)} + t_f$)	$t_{d (off)}$	—	330	430		$R_{GS} = 50\Omega$
	t_f	—	110	140		
Fast-recovery reverse diode						
Continuous reverse drain current	I_{DR}	—	—	6,5	A	$T_C = 25^{\circ}C$
Pulsed reverse drain current	I_{DRM}	—	—	26		
Diode forward on-voltage	V_{SD}	—	1,15	1,6	V	$I_F = 2 \times I_{DR}$ $V_{GS} = 0V, T_J = 25^{\circ}C$
Reverse recovery time	t_{rr}	—	180 220	250 300	ns	$T_J = 25^{\circ}C$ $T_J = 150^{\circ}C$
Reverse recovery charge	Q_{rr}	—	0,65 2,6	1,2 5,0	μC	$T_J = 25^{\circ}C$ $T_J = 150^{\circ}C$
Repetitive peak reverse current	I_{RRM}	—	—	—	A	$T_J = 25^{\circ}C$ $T_J = 150^{\circ}C$


SIEMENS AKTIENGESELLSCHAFT

Power dissipation $P_D = f(T_C)$ Typical output characteristics $I_D = f(V_{DS})$
parameter: 80 μ s pulse test,
 $T_J = 25^\circ\text{C}$ Safe operating area $I_D = f(V_{DS})$
parameter: $D = 0.01$, $T_C = 25^\circ\text{C}$ Typical transfer characteristic $I_D = f(V_{GS})$
parameter: 80 μ s pulse test,
 $V_{DS} = 25\text{V}$, $T_J = 25^\circ\text{C}$ 

SIEMENS AKTIENGESellschaft



Typical drain-source on-state resistance

$R_{DS(on)} = f(I_D)$


parameter: $V_{GS} = 10V$, $T_J = 25^\circ C$ 

Drain-source on-state resistance

$R_{DS(on)} = f(T_J)$


parameter: $I_D = 4.2A$, $V_{GS} = 10V$ (spread)Typical transconductance $g_{fs} = f(I_D)$ parameter: 80 μs pulse test, $V_{DS} = 25V$, $T_J = 25^\circ C$ Gate threshold voltage $V_{GS(th)} = f(T_J)$ parameter: $V_{DS} = V_{GS}$, $I_D = 1mA$

(spread)




— SIEMENS AKTIENGESELLSCHAFT —


Typical capacitances $C = f(V_{DS})$
parameter: $V_{GS} = 0$, $f = 1\text{MHz}$




Continuous drain current $I_D = f(T_C)$
parameter: $V_{GS} \geq 10\text{V}$



Forward characteristic of reverse diode
 $I_F = f(V_{SD})$
parameter: $T_j, t_p = 80 \mu\text{s}$
(spread)



Transient thermal impedance $Z_{thJC} = f(t)$
parameter: $D = t_p / T$



Typical gate-charge $V_{GS} = f(Q_{Gate})$
parameter: $I_{D\ puls} = 9A$

